WOLF OFFICIALTECH
10W-40 HYDRO HD

25/09/2026
65669

This is a SAE 10W-40 hydrogen-ICE heavy duty engine oil with protection and performance precisely tuned to hydrogen's unique demands.

APPLICATIONS

Specifically developed for hydrogen-ICE heavy duty engines.

FEATURES

Corrosion protection: high level of corrosion protection
Pre-ignition: prevents oil-related pre-ignition
Water handling: high level of water resistance

SPECIFICATIONS

/ /

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.861
Kinematic viscosity at 40°C	ASTM D445	mm²/s	88.0
Kinematic viscosity at 100°C	ASTM D445	mm²/s	13.8
Viscosity index	ASTM D2270		160
Pour point	ASTM D6892	°C	-45

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV