WOLF OFFICIALTECH
GL-4 75W-90 V

25/09/2026
2319

This is a full synthetic high-performance long drain, severe service manual transmission fluid capable of extending oil drain intervals to 800.000 kilometers.

APPLICATIONS

This severe service manual transmission fluid can be used in all overdrive Volvo I-shift transmissions and other heavy duty automated manual transmissions.
Also suitable for Mack mDrive transmissions.

FEATURES

Anti-wear protection: long transmission life
Oil life durability: high level of thermal and oxidation stability
Frictional properties: very smooth shift performance

SPECIFICATIONS

API	GL-4	MACK	TO-A PLUS
API	MT-1	MB	235.11
ALLISON	TES 439	NAVISTAR	MPAPS B-6816 TYPE 2
ARVIN MERITOR	O-81	VOLVO	97315
DTFR	13B110	VOLVO	97318
EATON	PS-386	VOLVO	97319

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.857
Kinematic viscosity at 40°C	ASTM D445	mm²/s	103
Kinematic viscosity at 100°C	ASTM D445	mm²/s	15.7
Viscosity index	ASTM D2270		162
Pour point	ASTM D6892	°C	-45
Flash Point COC	ASTM D92	°C	230

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV