WOLF OFFICIALTECH
5W30 UHPD

25/09/2026
65613

This is a full synthetic lubricant based on carefully selected very high quality base oils, which satisfies the highest performance standards for large trucks. The formulation includes a state of the art friction modifier for improved fuel economy.

APPLICATIONS

It is recommended for Euro V and most Euro VI engines. Perfectly compatible with all after-treatment systems and devices (EGR, SCR, DPF, etc.) in combination with low sulfur diesel (max 50 ppm).

FEATURES

Aftertreatment protection: the purpose is full aftertreatment system protection
Fuel economy: the purpose is good fuel economy and low exhaust emissions
Engine protection: high level of engine cleanliness and durability

SPECIFICATIONS

ACEA	E4-16	VOLVO	VDS-4
ACEA	E6-16		
ACEA	E7-16		
ACEA	E9-16		
API	CJ-4		
API	SN		
JASO	DH-2		
CATERPILLAR	ECF-3		
CUMMINS	CES 20081		
DETROIT DIESEL	DFS 93K218		
DEUTZ	DQC IV-10 LA		
MACK	EO-M PLUS		
MACK	EO-N Premium Plus		
MACK	EO-O Premium Plus		
MAN	M3271-1		
MAN	M3477		
MAN	M3575		
MAN	M3677		
MAN	M3691		
MB	235.28		
MTU	Oil Category 2.1		
MTU	Oil Category 3.1		
RENAULT	RGD		
RENAULT	RLD-2		
RENAULT	RLD-3		
RENAULT	RXD		
SCANIA	LDF-4		
VOITH	Retarder Oil Class B		
VOLVO	CNG		
VOLVO	VDS-3		

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.856
Kinematic viscosity at 40°C	ASTM D445	mm^2/s	68.9
Kinematic viscosity at 100°C	ASTM D445	mm^2/s	11.8
Viscosity index	ASTM D2270		168
B.N. (HCLO4 method)	ASTM D2896	mg KOH/g	12.8
Pour point	ASTM D6892	°C	-51
CCS viscosity at -30°C	ASTM D5293	mPa.s	5640
Sulfated Ash	ASTM D874	Mass %	1.0
Flash Point COC	ASTM D92	°C	222

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com