

WOLF ECOTECH DSG FLUID

01/12/2023
5080

This is a full synthetic lubricant based on carefully selected very high quality base oils, specifically developed for the dual clutch transmissions (DCT) of modern passenger cars. It ensures trouble-free operation of these gearboxes.

APPLICATIONS

Mainly intended for the DSG (Direct Shift Gearbox) of VAG, this fluid can also be used for other 6-speed DCT transmissions, such as Chrysler Powershift, Ford Powershift, Mitsubishi TC-SST, Volvo Powershift, BMW Drivelogic 7-speed, etc. This product is not intended for VW dry clutch DSG type 0AM, 02M, 02Q and 02S.

FEATURES

Anti-wear protection: significantly extended transmission life
Frictional properties: very smooth gear shifting, no vibration
Extended oil life: excellent thermal and oxidation stability

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com



SPECIFICATIONS

API	GL-4	NISSAN	LV MTF-1
BMW	83220306816	NISSAN	R35 SPECIAL
BMW	83220397244	PORSCHE	000.043.20
BMW	83220440214	PORSCHE	000.043.207.29
BMW	83222147477	PORSCHE	000.043.207.30
BMW	83222148578	PORSCHE	000.043.305.63
BMW	83222148579	PORSCHE	999.917.080.00
BMW	83222167666	PORSCHE	999.917.080.01
BMW	83222409710	PORSCHE	999.917.546.00
BMW	83222433157	PORSCHE	TF 0870
BMW	DCTF-1	PSA	1618078480
BMW	DCTF-2	PSA	9730 A8
BMW	DTF 1	PSA	9734 S2
BMW	FFL-4	PSA	JWS 2271
BMW	MTF LT-3	RENAULT	7711785243
BMW	MTF LT-5	RENAULT	BOT450 EDC 6-Speed
CHRYSLER	68044345EA	RENAULT	DC4
DAIMLER TRUCK	DTFR 13C130	RENAULT	DW5
FERRARI	TF DCT-F3	SUZUKI	99000-22B27-036
FIAT	9.55550-DA11	TOYOTA	JWS 2271
FIAT	9.55550-MZ2	TOYOTA	LF
FIAT	9.55550-MZ6	TOYOTA	LV 75W MT
FORD	F-DC	VOLVO	1161520-7
FORD	WSS-M2C200-D2	VOLVO	1161839
FORD	WSS-M2C200-D3	VOLVO	BOT341 #1161838
FORD	WSS-M2C200-E1	VW	G 009 317
FORD	WSS-M2C218-A1	VW	G 052 171
FORD	WSS-M2C936-A	VW	G 052 178
GM	FFL-4	VW	G 052 182
HONDA	MTF III	VW	G 052 512
MB	236.21	VW	G 052 513
MB	236.24	VW	G 052 527
MB	236.25	VW	G 052 529
MB	239.21	VW	G 052 726
MB	SLS A0019898603	VW	G 052 798
MCLAREN	FFL-4	VW	G 055 512
MITSUBISHI	DIAMOND QUEEN SSTF-1	VW	G 055 529
NISSAN	999MP-6TRT00P	VW	G 055 549
NISSAN	DCT FLUID	VW	G 060 726
NISSAN	GR6	VW	G 070 726
NISSAN	GT-R R35	VW	TL 521 82

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com



TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.848
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	33.6
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	6.87
Viscosity index	ASTM D2270		170
Pour point	ASTM D6892	°C	-45
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	11000
Flash Point COC	ASTM D92	°C	198

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

