WOLF VITALTECH 10W60

25/09/2026
24118

This is a semi synthetic lubricant based on carefully selected highly refined base oils. This engine oil of the latest generation is suitable for the lubrication of all gasoline and diesel engines with turbo. It is mainly used for severe duty use, like racing and hot climates. Its high viscosity ensures a perfect lubrication under those conditions.

APPLICATIONS

This oil is suitable for 4 stroke gasoline engines, multi-valves, turbo for severe services and 4 stroke diesel engines, with or without turbo.

FEATURES

Engine protection: ensures high level of the engine cleanliness
Cold start: high level of fluidity at low temperature

SPECIFICATIONS

ACEA	A3/B4	VW	501 01
API	SN/CF	VW	505 00

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.866
Kinematic viscosity at 40°C	ASTM D445	mm^2/s	171
Kinematic viscosity at 100°C	ASTM D445	mm^2/s	24.5
Viscosity index	ASTM D2270		175
B.N. (HCLO4 method)	ASTM D2896	mg KOH/g	9.6
Pour point	ASTM D6892	°C	-36
CCS viscosity at -25°C	ASTM D5293	mPa.s	6700
Sulfated Ash	ASTM D874	Mass %	1.1
Flash Point COC	ASTM D92	°C	238

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV