

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200



**Trade name: ZF-LIFEGUARDFLUID 6**

ZF Aftermarket

## 1. Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name: ZF-LIFEGUARDFLUID 6

Product code: S671.090.250  
S671.090.252  
S671.090.253  
S671.090.255

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture: Transmission oil.

Uses advised against: This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the supplier.

### 1.3 Details of the supplier of the safety data sheet

**ZF Friedrichshafen AG**  
**ZF Aftermarket**  
**Obere Weiden 12**  
**97424 Schweinfurt**  
**Germany**  
**+49 9721 475 60**  
**[www.zf.com/contact](http://www.zf.com/contact)**

### 1.4 Emergency telephone number

**24/7h Emergency telephone number:**

+49 (0)89 19240 Information in German and English

---

## 2. Hazards identification

### 2.1 Classification of the substance or mixture

**Classification GHS**

Chronic aquatic toxicity, Category 3

### 2.2 Label elements

**GHS Labelling**

Hazard pictograms: No Hazard Symbol required

Signal word: No signal word

Hazard statements



**Trade name: ZF-LIFEGUARDFLUID 6**

ZF Aftermarket

PHYSICAL HAZARDS:	Not classified as a physical hazard according to GHS criteria.
HEALTH HAZARDS:	Not classified as a health hazard under GHS criteria.
ENVIRONMENTAL HAZARDS:	H412 Harmful to aquatic life with long lasting effects.
Precautionary statements:	
<b>Prevention:</b>	P273 Avoid release to the environment.
<b>Response:</b>	No precautionary phrases.
<b>Storage:</b>	No precautionary phrases.
<b>Disposal:</b>	P501 Dispose of contents/ container to an approved waste disposal plant.

**2.3 Other hazards which do not result in classification**

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.  
Used oil may contain harmful impurities.  
Not classified as flammable but will burn.

The classification of this material is based on OSHA HCS 2012 criteria.

---

**3. Composition/information on ingredients**

**3.2 Mixtures**

Chemical nature	Synthetic base oil and additives. Highly refined mineral oil. The highly refined mineral oil contains <3% (w/w) DMSO extract, according to IP346. The highly refined mineral oil is only present as additive diluent.
-----------------	--

\* contains one or more of the following CAS-numbers:  
64742-53-6, 64742-54-7, 64742-55-8,  
64742-56-9, 64742-65-0, 68037-01-4,  
72623-86-0, 72623-87-1, 8042-47-5,  
848301-69-9.

**Hazardous components**



**Trade name: ZF-LIFEGUARDFLUID 6**

ZF Aftermarket

---

#### **4. First aid measures**

##### **4.1 Description of first aid measures**

General advice:	Not expected to be a health hazard when used under normal conditions.
Protection of first-aiders:	When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
Immediate medical attention, special treatment:	Treat symptomatically.
If inhaled:	No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
In case of skin contact:	Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.
In case of eye contact:	Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue rinsing. If persistent irritation occurs, obtain medical attention.
If swallowed:	In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.

##### **4.2 Most important symptoms and effects, both acute and delayed**

Symptoms:	Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.
-----------	---

##### **4.3 Indication of any immediate medical attention and special treatment needed**

Treatment:	Notes to doctor/physician: Treat symptomatically.
------------	--

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200



**Trade name: ZF-LIFEGUARDFLUID 6**

ZF Aftermarket

## 5. Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media: Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media: Do not use water in a jet.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting: Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.

### 5.3 Advice for firefighters

Special protective equipment for firefighters: Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

Specific extinguishing methods: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

---

## 6. Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions: For non emergency personnel:  
Avoid contact with skin and eyes.

Emergency responders: For emergency responders:  
Avoid contact with skin and eyes.

## SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200



**Trade name: ZF-LIFEGUARDFLUID 6**

ZF Aftermarket

### 6.2 Environmental precautions

Environmental precautions:

Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Local authorities should be advised if significant spillages cannot be contained.

### 6.3 Methods and materials for containment and cleaning up

Methods for cleaning up:

Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly

### 6.4 Reference to other sections

For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet.

For guidance on disposal of spilled material see Chapter 13 of this Safety Data Sheet.

---

## 7. Handling and storage

General Precautions:

Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

### 7.1 Precautions for safe handling

Advice on safe handling:

Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags



**Trade name: ZF-LIFEGUARDFLUID 6**

ZF Aftermarket

	or cleaning materials in order to prevent fires.
Avoidance of contact:	Strong oxidising agents.
Product Transfer:	This material has the potential to be a static accumulator. Proper grounding and bonding procedures should be used during all bulk transfer operations.
Fire-fighting class:	Fires involving liquids or liquid containing substances. Also includes substances which become liquid at elevated temperatures.

**7.2 Conditions for safe storage, including any incompatibilities**

Other data:	Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers. Store at ambient temperature.
Packaging material:	Suitable material: For containers or container linings, use mild steel or high density polyethylene. Unsuitable material: PVC.
Container Advice:	Polyethylene containers should not be exposed to high temperatures because of possible risk of distortion.

**8. Exposure controls/personal protection**

**8.1 Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Oil mist, mineral	Not Assigned	TWA ((inhalable fraction))	5 mg/m <sup>3</sup>	US. ACGIH Threshold Limit Values
		(Mist)	5 mg/m <sup>3</sup>	OSHA_TRANS

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200



Trade name: ZF-LIFEGUARDFLUID 6

ZF Aftermarket

		TWA (Mist)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m <sup>3</sup>	ACGIH

## Biological occupational exposure limits

No biological limit allocated.

## Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods

<http://www.cdc.gov/niosh/>

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods

<http://www.osha.gov/>

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances

<http://www.hse.gov.uk/>

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany

<http://www.dguv.de/inhalt/index.jsp>

L'Institut National de Recherche et de Sécurité, (INRS), France

<http://www.inrs.fr/accueil>

## 8.2 Exposure controls Engineering measures

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

General Information:

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

## SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200



**Trade name: ZF-LIFEGUARDFLUID 6**

ZF Aftermarket

---

Drain down system prior to equipment break-in or maintenance.  
Retain drain downs in sealed storage pending disposal or subsequent recycle.  
Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping

### **Personal protective equipment**

#### **Respiratory protection:**

No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for the combination of organic gases and vapours [Type A/Type P boiling point >65°C (149°F)].

#### **Eye protection:**

If material is handled such that it could be splashed into eyes, protective eyewear is recommended.

#### **Hand protection:**

Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean



## SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200



**Trade name: ZF-LIFEGUARDFLUID 6**

ZF Aftermarket

hands. After using gloves, hands should be washed and dried thoroughly.

Application of a non-perfumed moisturizer is recommended.

For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same, but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material.

Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.

### **Skin and body protection:**

Skin protection is not ordinarily required beyond standard work clothes.

It is good practice to wear chemical resistant gloves.

### **Respiratory protection:**

No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers.

Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined particulate/organic gases and vapours [Type A/Type P boiling point > 65°C (149°F)] meeting EN14387 and EN143.

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200



Trade name: ZF-LIFEGUARDFLUID 6

ZF Aftermarket

**Thermal hazards:**

Not applicable

**Protective measures:**

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

**Environmental exposure controls**

General advice:

Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Chapter 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water. Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.

## 9. Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance: Liquid at room temperature  
Colour: amber  
Odour: Slight hydrocarbon  
Odour Threshold: Data not available  
pH: Not applicable

Pour point	-30 °C / -22 °F	ASTM D97
Initial boiling point and boiling range	> 280 °C / 536 °F estimated value(s)	
Flash point	230°C / 446 °F	ASTM D92 (COC)
Evaporation rate	Data not available	
Flammability (solid, gas)	Data not available	
Upper explosion limit	Typical 10 %(V)	
Lower explosion limit	Typical 1 %(V)	

**SAFETY DATA SHEET**

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

**Trade name: ZF-LIFEGUARDFLUID 6**

ZF Aftermarket

Vapour pressure	< 0,5 Pa (20 °C / 68 °F) estimated value(s)	
Relative vapour density	> 1 estimated value(s)	
Relative density	0,840 (15°C / 59 °F)	
Density	840 kg/m <sup>3</sup> (15°C / 59 °F)	ASTM D4052
<b>Solubility(ies)</b>		
Water solubility	negligible	
Solubility in other solvents	Data not available	
Partition coefficient: n-octanol/water	Pow: > 6 (based on information on similar products)	
Auto-ignition temperature	> 320 °C / 608 °F	
Viscosity, dynamic	Data not available	
Viscosity, kinematic	26,8 mm <sup>2</sup> /s (40 °C / 104 °F) 5,6 mm <sup>2</sup> /s (100°C / 212 °F)	ISO 3104
Explosive properties	Not classified	
Oxidizing properties	Data not available	

**9.2 Other information**

Conductivity:

This material is not expected to be a static accumulator.

Decomposition temperature:

Data not available

**10. Stability and reactivity**

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200



**Trade name: ZF-LIFEGUARDFLUID 6**

ZF Aftermarket

- |   |   |
|---|---|
| <b>10.1 Reactivity</b>                          | The product does not pose any further reactivity hazards in addition to those listed in the following subparagraph. |
| <b>10.2 Chemical stability:</b>                 | Stable.   |
| <b>10.3 Possibility of hazardous reactions:</b> | Reacts with strong oxidising agents.  |
| <b>10.4 Conditions to avoid:</b>                | Extremes of temperature and direct sunlight   |
| <b>10.5 Incompatible materials:</b>             | Strong oxidising agents.  |
| <b>10.6 Hazardous decomposition products:</b>   | Hazardous decomposition products are not expected to form during normal storage.                                    |

---

## 11. Toxicological information

### 11.1 Information on toxicological effects

Basis for assessment:	Information given is based on data on the components and the toxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
-----------------------	---

Information on likely routes of exposure	Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.
--	---

#### Acute toxicity

Product: Acute oral toxicity:	LD50 rat: > 5.000 mg/kg Remarks: Expected to be of low toxicity
----------------------------------	--

Acute inhalation toxicity:	Remarks: Not considered to be an inhalation hazard under normal conditions of use.
----------------------------	--

Acute dermal toxicity:	LD50 Rabbit: > 5.000 mg/kg Remarks: Expected to be of low toxicity
------------------------	---

#### Skin corrosion/irritation

Product: Remarks: Expected to be slightly irritating. Prolonged or repeated skin contact	
---	--



**Trade name: ZF-LIFEGUARDFLUID 6**

ZF Aftermarket

without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

**Serious eye damage/eye irritation**

Product:

Remarks: Expected to be slightly irritating.

**Respiratory or skin sensitisation**

Product:

Remarks: Not expected to be a sensitiser.

**Germ cell mutagenicity**

Product:

Remarks: Not considered a mutagenic hazard.

**Carcinogenicity**

Product:

Remarks: Not expected to be carcinogenic.

**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**ACGIH**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Reproductive toxicity**

Product:

Remarks: Not expected to impair fertility.

Not expected to be a developmental toxicant.

**STOT - single exposure**

Product:

Remarks: Not expected to be a hazard.

**STOT - repeated exposure**

Product:

Remarks: Not expected to be a hazard.

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200



**Trade name: ZF-LIFEGUARDFLUID 6**

ZF Aftermarket

## Aspiration toxicity

Product:

Not considered an aspiration hazard.

## Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal. ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Slightly irritating to respiratory system.

---

## 12. Ecological information

### 12.1 Ecotoxicity

Basis for assessment:

Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s). (LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract).

Product:

Toxicity to fish (Acute toxicity):

Remarks: Expected to be harmful:  
LL/EL/IL50 10-100 mg/l

Toxicity to daphnia and other aquatic invertebrates (Acute toxicity)

Remarks: Expected to be harmful:  
LL/EL/IL50 10-100 mg/l

Toxicity to algae (Acute toxicity)

Remarks: Expected to be harmful:  
LL/EL/IL50 10-100 mg/l

Toxicity to fish (Chronic toxicity)

Remarks: Data not available

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)

Remarks: Data not available

Toxicity to bacteria (Acute toxicity)

Remarks: Data not available

### 12.2 Persistence and degradability

Product:

Biodegradability

Remarks: Expected to be not readily biodegradable. Major constituents are ex-

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200



**Trade name: ZF-LIFEGUARDFLUID 6**

ZF Aftermarket

pected to be inherently biodegradable, but contains components that may persist in the environment.

## 12.3 Bioaccumulative potential

Product:  
Bioakkumulation

Remarks: Contains components with the potential to bioaccumulate.

## 12.4 Mobility in soil

Product:  
Mobility

Remarks: Liquid under most environmental conditions. If it enters soil, it will adsorb to soil particles and will not be mobile.

Remarks: Floats on water.

## 12.5 Other adverse effects

Product:  
Additional ecological information

Product is a mixture of non-volatile components, which are not expected to be released to air in any significant quantities. Not expected to have ozone depletion potential, photochemical ozone creation potential or global warming potential.

Poorly soluble mixture. May cause physical fouling of aquatic organisms.

---

## 13. Disposal considerations

### 13.1 Waste treatment methods

Product:

Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in water courses.

Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.

Waste, spills or used product is dangerous waste.

Contaminated packaging:

Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be estab-



**Trade name: ZF-LIFEGUARDFLUID 6**

ZF Aftermarket

lished beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Local legislation Remarks:

Disposal should be in accordance with applicable regional, national, and local laws and regulations.

---

## 14 Transport information

### 14.1 National Regulations

US Department of Transportation Classification (49 CFR Parts 171-180): Not regulated as a dangerous good

### 14.2 International Regulations

IATA-DGR Not regulated as a dangerous good  
IMDG-Code Not regulated as a dangerous good

### 14.3 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Pollution category Not applicable  
Ship type Not applicable  
Product name Not applicable  
Special precautions Not applicable

### 14.4 Special precautions for user

Remarks: Special Precautions: Refer to Chapter 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

### 14.5 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Pollution category: Not applicable  
Ship type: Not applicable  
Product name: Not applicable  
Special precautions: Not applicable  
Additional Information: MARPOL Annex 1 rules apply for bulk shipments by sea.

---

## 15. Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

OSHA Hazards

No OSHA Hazards



## SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200



**Trade name: ZF-LIFEGUARDFLUID 6**

ZF Aftermarket

EPCRA - Emergency Planning and Community Right-to-Know Act

### **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ. Shell classifies this material as an "oil" under the CERCLA Petroleum Exclusion, therefore releases to the environment are not reportable under CERCLA.

### **SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

### **SARA 311/312 Hazards**

No SARA Hazards

### **SARA 302**

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

### **SARA 313**

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

### **Clean Water Act**

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

### **Pennsylvania Right To Know**

Diphenylamine 122-39-4

### **California Prop 65**

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

### **The components of this product are reported in the following inventories:**

EINECS: All components listed or polymer exempt.

TSCA: All components listed.

DSL: Notified with Restrictions.

---

## **16. Other information**

### **Further information**

**NFPA Rating (Health, Fire, Reactivity) 0,1,0**

Abbreviations and Acronyms:

The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific

## SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200



**Trade name: ZF-LIFEGUARDFLUID 6**

ZF Aftermarket

dictionaries) and/or websites.

ACGIH = American Conference of Governmental Industrial Hygienists

ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road

AICS = Australian Inventory of Chemical Substances

ASTM = American Society for Testing and Materials

BEL = Biological exposure limits

BTEX = Benzene, Toluene, Ethylbenzene, Xylenes

CAS = Chemical Abstracts Service

CEFIC = European Chemical Industry Council

CLP = Classification Packaging and Labelling

COC = Cleveland Open-Cup

DIN = Deutsches Institut für Normung

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

DSL = Canada Domestic Substance List

EC = European Commission

EC50 = Effective Concentration fifty

ECETOC = European Center on Ecotoxicology and Toxicology Of Chemicals

ECHA = European Chemicals Agency

EINECS = The European Inventory of Existing Commercial Chemical Substances

EL50 = Effective Loading fifty

ENCS = Japanese Existing and New Chemical Substances Inventory

EWC = European Waste Code

GHS = Globally Harmonised System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IC50 = Inhibitory Concentration fifty

IL50 = Inhibitory Level fifty

IMDG = International Maritime Dangerous Goods

INV = Chinese Chemicals Inventory

IP346 = Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables

KECI = Korea Existing Chemicals Inventory

## SAFETY DATA SHEET

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200



**Trade name: ZF-LIFEGUARDFLUID 6**

ZF Aftermarket

LC50 = Lethal Concentration fifty  
LD50 = Lethal Dose fifty per cent.  
LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading  
LL50 = Lethal Loading fifty  
MARPOL = International Convention for the Prevention of Pollution From Ships  
NOEC/NOEL = No Observed Effect Concentration / No Observed Effect Level  
OE\_HPVS = Occupational Exposure - High Production Volume  
PBT = Persistent, Bioaccumulative and Toxic  
PICCS = Philippine Inventory of Chemicals and Chemical Substances  
PNEC = Predicted No Effect Concentration  
REACH = Registration Evaluation And Authorisation Of Chemicals  
RID = Regulations Relating to International Carriage of Dangerous Goods by Rail  
SKIN\_DES = Skin Designation  
STEL = Short term exposure limit  
TRA = Targeted Risk Assessment  
TSCA = US Toxic Substances Control Act  
TWA = Time-Weighted Average  
vPvB = very Persistent and very Bioaccumulative

### Further information

Training advice:

Provide adequate information, instruction and training for operators.

Other information:

A vertical bar (|) in the left margin indicates an amendment from the previous version.

Sources of key data used to compile the Safety Data Sheet

The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID data base, EC 1272 regulation, etc).

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.