

WOLF OFFICIALTECH 5W30 C3 SP EXTRA

11/08/2023
65648

This is a full synthetic lubricant based on carefully selected very high quality base oils, formulated using the latest technology for catalyst compatible engine oils. Its special formulation combines fuel economy with an extended service life. The reduced ash formulation protects particulate filters and exhaust after-treatment devices.

APPLICATIONS

This dexos 2™ is required for all new GM/Opel/Vauxhall/Chevrolet diesel and gasoline models. GM/Opel has advised that the dexos 2™ specification is backward compatible to older GM/Opel specifications (GM-LL-A-025 and GM-B-LL-025). The majority of GM/Opel/Vauxhall/Chevrolet diesel and gasoline vehicles can use dexos 2™ lubricants. Broad application field with both ACEA C3/C2 and also covering API SP.

FEATURES

Total engine protection: outstanding engine cleanliness and durability.

Fuel economy: lower fuel consumption and CO2 emissions.

Aftertreatment protection: full aftertreatment device protection.

PERFORMANCE

ACEA	C2	KIA	.
ACEA	C3	MB	approval 229.31
API	approval SN Plus	MB	approval 229.51
API	approval SP	MB	approval 229.52
BMW	approval LONGLIFE-04	OPEL	approval OV 040 1547 - D30
CHRYSLER	MS 11106	OPEL	approval OV 040 1547 - G30
FIAT	9.55535-S1	OPEL	GM-LL-A-025
FIAT	9.55535-S3	OPEL	GM-LL-B-025
FORD	WSS-M2C917-A	RENAULT	RN 0700
GM	dexos 2	RENAULT	RN 0710
GM	dexos1™ Gen 2	VW	505 00
HYUNDAI	.	VW	505 01
IVECO	18-1811 Classe SC1		

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com



TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.853
Kinematic viscosity at 40°C	ASTM D445	mm²/s	68.7
Kinematic viscosity at 100°C	ASTM D445	mm²/s	11.6
Viscosity index	ASTM D2270		164
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	7.5
Pour point	ASTM D6892	°C	-39
Flash Point COC	ASTM D92	°C	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

