WOLF GUARDTECH 15W40 SL/CF

06/10/2026
14136

This is a very high-quality mineral oil with proven performance. It has been upgraded to meet and exceed ACEA A3/B4-08. It is suitable for most 4-stroke gasoline and diesel cars as well as light trucks.

APPLICATIONS

4-stroke gasoline passenger cars engines (multi-valve, turbo, etc.); 4-stroke diesel engines, with or without turbo. High compatibility with biodiesel, based on extensive field trials.

FEATURES

Engine protection: engine protection and cleanliness

SPECIFICATIONS

ACEA	A3/B3	MB	229.1
ACEA	A3/B4	PSA	B71 2295
API	SL/CF	VW	501 01 Level
FIAT	9.55535-D2	VW	505 00 Level
FIAT	9.55535-G2		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.875
Kinematic viscosity at 40°C	ASTM D445	mm^2/s	94.0
Kinematic viscosity at 100°C	ASTM D445	mm^2/s	13.7
Viscosity index	ASTM D2270		148
B.N. (HCLO4 method)	ASTM D2896	mg KOH/g	10.1
Pour point	ASTM D6892	°C	-36
CCS viscosity at -20°C	ASTM D5293	mPa.s	4100
Sulfated Ash	ASTM D874	Mass %	1.3
Flash Point COC	ASTM D92	°C	230

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV