

WOLF ESSENTIAL SN/CF C3 5W40 PI

21/07/2025
75608

This full synthetic engine oil meets the core requirements of ACEA and API for passenger cars. It keeps soot particles dispersed and prevents the formation of piston deposits.

APPLICATIONS

This engine oil is recommended for direct injection diesel engines, including common rail direct fuel injection systems with or without aftertreatment system.

FEATURES

Aftertreatment protection: full aftertreatment system protection.
Total engine protection: outstanding engine cleanliness and durability.

SPECIFICATIONS

ACEA	C3	MB	229.51
API	CF	OPEL	OV 040 1547 - D40
API	SN	PORSCHE	A40
BMW	LOGLIFE-04	RENAULT	RN 0700
FORD	WSS-M2C917-A	RENAULT	RN 0710
GM	dexos 2	VW	505 00
MB	229.31	VW	505 01

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.849
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	80.5
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	13.8
Viscosity index	ASTM D2270		177
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	6.8
Pour point	ASTM D6892	°C	-42

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com

