WOLF HYDRAULIC
HLP-D ISO 46

25/09/2026
4026

This is a mineral oil-based hydraulic fluid containing a selective additive system, for protection of hydraulic systems, plus the addition of detergent/dispersant additives. It meets the HLPD requirements.

APPLICATIONS

This oil is suited for use in hydraulic systems, where due to high ingresses of water or contamination a high level of dispersancy is required to prevent water dropout in the system.

FEATURES

Anti-wear and oxidation stability: high level of protection
Anti-foam properties: very good anti-foam properties
Temperature stability: high viscosity stability

SPECIFICATIONS

DIN	51524 T2 HLPD	MAN	N698-H-LPD

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.879
Kinematic viscosity at 40°C	ASTM D445	mm²/s	49.7
Kinematic viscosity at 100°C	ASTM D445	mm²/s	7.4
Viscosity index	ASTM D2270		110
Pour point	ASTM D6892	°C	-27
Flash Point COC	ASTM D92	°C	210

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com