

WOLF OFFICIALTECH 10W-30 UHPD MF

14/08/2023
15765

This oil for gas powered HD engines offers exceptional wear resistance. It is capable of maintaining its original composition thanks to its outstanding oxidation resistance, shear resistance and aeration control, giving it an increased drain interval compared to previous formulations.

APPLICATIONS

Both modern and older gas powered engines benefit from this heavy-duty engine oil for most OEMs, making it a perfect match for a wide range of engine types. It is capable of offering optimal protection to a range of Caterpillar, Mack, Renault, Volvo and other market-leading engines with or without after-treatment system, turbo- or supercharger. It is compatible with emission control technology EURO IV, V and VI for trucks; as well as stage IIIB, IV and Tier 4i, 4f for heavy-duty off-road.

FEATURES

Improved engine cleanliness: increased operating hours
High wear protection: increased engine lifespan
Increased oxidative stability: extended optimal oil performance

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com



PERFORMANCE

ACEA	E11	DEUTZ	DQC-III-10 LA
ACEA	E6-16	DEUTZ	DQC-III-18 LA
ACEA	E7	DEUTZ	DQC-IV-18 LA
ACEA	E8	FORD	WSS-M2C171-F1
ACEA	E9-16	IVECO	18-1804 Classe T2 E7
API	approval CK-4	IVECO	18-1804 Classe TLS E9
API	CI-4	JD	JDQ-78X
API	CJ-4	LIEBHERR	LH-00-ENG5C LA
API	SN	MACK	EO-M PLUS
JASO	DH-1	MACK	EO-N
JASO	DH-2	MACK	EO-N Premium Plus
ALLISON	C4	MACK	EO-O Premium Plus
API	CI-4 Plus	MACK	EO-S 4.5
CATERPILLAR	ECF-1a	MAN	M3271-1
CATERPILLAR	ECF-2	MAN	M3477
CATERPILLAR	ECF-3	MAN	M3575
CATERPILLAR	TO-2	MAN	M3775
CUMMINS	CES 20076	MB	228.3
CUMMINS	CES 20077	MB	228.31
CUMMINS	CES 20078	MB	228.51
CUMMINS	CES 20081	MB	228.52
CUMMINS	CES 20085	MB	235.28
CUMMINS	CES 20086	MTU	Oil Category 2.1
CUMMINS	CES 20092	MTU	Oil Category 3.1
DAF	EXTENDED DRAIN	RENAULT	RGD
DAF	PSQL 2.1 E	RENAULT	RLD
DAF	PSQL 2.1 E LD	RENAULT	RLD-2
DAIMLER TRUCK	DTFR 13D110	RENAULT	RLD-3
DAIMLER TRUCK	DTFR 15B110	RENAULT	RLD-4
DAIMLER TRUCK	DTFR 15C100	RENAULT	RXD
DAIMLER TRUCK	DTFR 15C110	SCANIA	LA
DAIMLER TRUCK	DTFR 15C120	VOITH	Retarder Oil Class B
DETROIT DIESEL	DFS 93K215	VOLVO	VDS-3
DETROIT DIESEL	DFS 93K218	VOLVO	VDS-4
DETROIT DIESEL	DFS 93K222	VOLVO	VDS-4.5
DEUTZ	DQC IV-10 LA		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.862
Kinematic viscosity at 40°C	ASTM D445	mm²/s	76.5
Kinematic viscosity at 100°C	ASTM D445	mm²/s	12.0
Viscosity index	ASTM D2270		153
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	10.2
Pour point	ASTM D6892	°C	-42
Flash Point COC	ASTM D92	°C	222

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com

