WOLF RACING
ESTER 0W-40 MS

25/09/2026
65516

This sustainable RRBO racing oil, fortified with ester and PAO, increases total engine protection.
It contains a precisely balanced component-blended additive system with high anti-wear and friction reducing characteristics.

APPLICATIONS

This sustainable advanced engine oil is specifically developed for race engines which operate over a wide range of temperatures and rpm.
The powerful formulation covers a large part of the racing car market thanks to its high-end properties.

FEATURES

Engine protection: ensures high level of the engine cleanliness
Driving conditions: sporty driving

SPECIFICATIONS

API	SN Plus	FORD	ST-SERIES
API	SP	FORD	WSS-M2C937-A
ASTON MARTIN	GT3	MB	AMG-SERIES
BMW	M-SERIES	PORSCHE	C40 GT
CHRYSLER	MS A0921	VOLVO	T-SERIES
FORD	RS-SERIES		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.852
Kinematic viscosity at 40°C	ASTM D445	mm^2/s	83.2
Kinematic viscosity at 100°C	ASTM D445	mm^2/s	14.5
Viscosity index	ASTM D2270		182
Pour point	ASTM D6892	°C	-42
Colour	VISUAL		DARK GREEN

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV