WOLF OFFICIALTECH
5W40 UHPD S

25/09/2026
15707

This is a synthetic lubricant based on carefully selected very high quality base oils, which satisfies the highest performance standards for large trucks. It can be used for engines equipped with after treatment systems.

APPLICATIONS

Due to its versatile specification levels it is suitable for a wide range of commercial vehicles. Specifically recommended for large truck engines to satisfy the EURO VI standard, TIER IV interim, TIER IV final, TIER V , stage IIIB, stage IV, stage V. It specifically includes the Chrysler MS 10902 application.

FEATURES

Aftertreatment protection: the purpose is full aftertreatment system protection
Engine protection: high level of engine protection

SPECIFICATIONS

ACEA	E11	DEUTZ	DQC-III-10 LA
ACEA	E6-16	DEUTZ	DQC-III-18 LA
ACEA	E7	DEUTZ	DQC-IV-18 LA
ACEA	E8	DTFR	13D110
ACEA	E9-16	DTFR	15C100
API	CI-4	DTFR	15C110
API	CI-4 Plus	DTFR	15C120
API	CJ-4	FORD	WSS-M2C171-E
API	CK-4	FORD	WSS-M2C171-F1
API	SN	IVECO	18-1804 Classe T2 E7
JASO	DH-1	IVECO	18-1804 Classe TLS E9
JASO	DH-2	JCB	Standard 4001/2700
AGCO/ALLIS	POWER LOCC-G2	JD	JDQ-78X
ALLISON	C4	LIEBHERR	LH-00-ENG5C LA
CATERPILLAR	ECF-1a	MACK	EO-M PLUS
CATERPILLAR	ECF-2	MACK	EO-N
CATERPILLAR	ECF-3	MACK	EO-N Premium Plus
CATERPILLAR	TO-2	MACK	EO-O Premium Plus
CHRYSLER	MS 10902	MACK	EO-S 4.5
CUMMINS	CES 20076	MAN	M3271-1
CUMMINS	CES 20077	MAN	M3477
CUMMINS	CES 20078	MAN	M3575
CUMMINS	CES 20081	MAN	M3775
CUMMINS	CES 20086	MB	235.28
CUMMINS	CES 20092	MTU	Oil Category 2.1
DAF	EXTENDED DRAIN	MTU	Oil Category 3.1
DETROIT DIESEL	DFS 93K215	RENAULT	RGD
DETROIT DIESEL	DFS 93K218	RENAULT	RLD
DETROIT DIESEL	DFS 93K222	RENAULT	RLD-2
DEUTZ	DQC IV-10 LA	RENAULT	RLD-3

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

RENAULT	RLD-4	VOLVO	VDS-3
RENAULT	RXD	VOLVO	VDS-4
SCANIA	LA	VOLVO	VDS-4.5
VOITH	Retarder Oil Class B		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.854
Kinematic viscosity at 40°C	ASTM D445	mm^2/s	84.3
Kinematic viscosity at 100°C	ASTM D445	mm^2/s	13.9
Viscosity index	ASTM D2270		170
B.N. (HCLO4 method)	ASTM D2896	mg KOH/g	10.2
Pour point	ASTM D6892	°C	-39
Flash Point COC	ASTM D92	°C	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com