WOLF OFFICIALTECH
ATF D/M ULV

25/09/2026
3027

This is a full synthetic lubricant based on carefully selected very highly refined base oils for automatic transmissions with a high viscosity index, excellent oxidation stability, excellent friction and anti-wear properties providing supreme fuel economy and meeting the requirements of most of the newest Ford and GM automatic transmissions.

APPLICATIONS

This fluid is a new ultra-low viscosity ATF for MY 2017 on, GM Hydra-Matic 10L90 (10Lxx series) speed automatic transmissions used in the Yukon, Camaro ZL-1, Cadillac Corvette, Tahoe and other rear wheel drive models. It is used in the Ford Raptor and F-150, and known as the 10R80. Ford ATF equivalent known as Mercon ULV and WSS-M2C949-A.

FEATURES

Anti-wear protection: long transmission life
Frictional properties: very smooth gear shifting, no vibration
Oil life durability: high level of thermal and oxidation stability

SPECIFICATIONS

AISIN-WARNER	AW-2
FORD	10R80
FORD	196825
FORD	2 537 413
FORD	2179725
FORD	2537407
FORD	HU7J M2C949 AB
FORD	HU7J M2C949 BA
FORD	MERCON ULV
FORD	WSS-M2C949-A
FORD	XT-12-QULV
GM	10L90
GM	19352619
GM	DEXRON ULV
GM	GM9986396
GM	GMW16954
MAZDA	ATF A7
NISSAN	MATIC-P
VW	G 060 540
VW	G F53 006 M2
VW	G F53 007 M4

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.847
Kinematic viscosity at 40°C	ASTM D445	mm^2/s	19.8
Kinematic viscosity at 100°C	ASTM D445	mm^2/s	4.55
Viscosity index	ASTM D2270		151
Pour point	ASTM D6892	°C	-51
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	3700
Flash Point COC	ASTM D92	°C	182
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV