WOLF OE LEVELTECH 5W30 C4

25/09/2026
75614

This full synthetic engine oil is formulated to meet the specifications of different OEMs. The low SAPS formula guarantees complete DPF protection. Furthermore, its fluidity at low temperatures guarantee easy starting in winter conditions.

APPLICATIONS

Can be used for gasoline and diesel engines of passenger cars, more specifically for Renault, requiring the ACEA C4 and RN 720 specifications.

FEATURES

Aftertreatment protection: aftertreatment system compatible
Engine protection: high level of engine cleanliness and durability

SPECIFICATIONS

ACEA	C3	MB	229.31
ACEA	C4	MB	229.51
FIAT	9.55535-S4	RENAULT	RN 0720
MB	226.51	SUZUKI	SFU

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.851
Kinematic viscosity at 40°C	ASTM D445	mm^2/s	69.1
Kinematic viscosity at 100°C	ASTM D445	mm^2/s	11.7
Viscosity index	ASTM D2270		165
B.N. (HCLO4 method)	ASTM D2896	mg KOH/g	7.2
Pour point	ASTM D6892	°C	-45
Sulfated Ash	ASTM D874	Mass %	0.5
Flash Point COC	ASTM D92	°C	222

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV