


**Anziehvorschrift Zylinderkopf****Tightening Instructions for Cylinder Head****Instructions de serrage pour culasse****Prescripciones de apriete para culatas****071.293**passend für / suitable for  
adaptable à / adaptable a**Renault / Dacia / Nissan****Das Original**Schraubenkopf / Head shape Anziehreihenfolge/Tightening sequence/Ordre de serrage/Orden de apriete  
Tête de vis / Cabeza de tornillo151.890  
M 10x1,5x117Anziehen/  
Tightening/  
Serrage/  
Apriete 20 Nm  
 240°±6°**Zeichenerklärung / Explanations / Explication / Explicacion**

	neue Zylinderkopfschrauben verwenden	use new cylinder head bolts	utiliser des vis neuves	emplar tornillos nuevos
*	Warmlauf (80°C)	warm up time (80°C)	chauffage (80°C)	calentamiento (80°C)
	Schrauben einzeln lösen und wieder anziehen	loosen and tighten each bolt	deserrer et serrer vis par vis	aflojar y apretar tornillo a tornillo
●	Setzzeit	relaxation time	durée de tassement	tiempo de espera
	Drehwinkel	torque angle	angle de serrage	ángulo de giro

**Motortyp / Engine type / Type de moteur / Tipo de motor**

Ø: 80 mm; 1.4-1.6 ltr. 16V

Mot: K4J 700, 710-714, 730, 732, 740, 750, 770

K4M 690, 700, 701, 704, 708-711, 714, 720

724, 740, 744-748, 750, 753-754, 760-764

Logan, Kubistar, Clio,  
Kangoo, Laguna, Megane**Elring-Serviceteam**

Fon +49 7123 724 799

Fax +49 7123 724 798

service@elring.de

24/11/12

**\*071.293\***