WOLF OFFICIALTECH ATF MB

25/09/2026
3011

This is a full synthetic lubricant based on carefully selected very high quality base oils, mainly intended for all MB 7-speed automatic transmissions and NAG-V Sport transmissions. It provides excellent frictional durability and superior performance.

APPLICATIONS

This ATF is recommended for the 7G-Tronic and 5-Speed automatic transmissions of Mercedes-Benz. Due to its specific composition and characteristics,it is not suitable for other applications.

FEATURES

Anti-wear protection: long transmission life
Frictional properties: very smooth gear shifting, no vibration
Oil life durability: high level of thermal and oxidation stability

SPECIFICATIONS

MB	236.14

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.850
Kinematic viscosity at 40°C	ASTM D445	mm²/s	31.3
Kinematic viscosity at 100°C	ASTM D445	mm²/s	6.3
Viscosity index	ASTM D2270		157
Pour point	ASTM D6892	°C	-45
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	<=20000
Flash Point COC	ASTM D92	°C	206
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV