WOLF ECOTECH
CVT-ATF FLUID

25/09/2026
3029

This is a multifunctional full synthetic lubricant that has been designed for both CVT and step automatic transmissions. The multi-vehicle suitability of this oil enables optimized supply chain, reduced operational cost and mitigated misapplication risk.
It offers outstanding anti-wear protection and stable friction characteristics.

APPLICATIONS

It is suitable for continuously variable transmissions (using steel push-belts or chains) and for the latest generation of high efficiency step automatic transmissions where the manufacturer recommends the specifications as referred to in the extensive list on this technical data sheet.

FEATURES

Anti-wear protection: long transmission life
Oil life durability: high level of thermal and oxidation stability
Frictional properties: very smooth gear shifting, no vibration

SPECIFICATIONS

JASO	M315-2013 1A
JASO	M315-2013 1A-LV
JASO	M315-2013 2A
ACURA	ATF-Z1
AISIN-WARNER	AW-1
AISIN-WARNER	AW-2
AISIN-WARNER	JWS 3309(T-IV)
AISIN-WARNER	JWS 3324(WS)
ALLISON	C3
ALLISON	C4
AUDI	TL 52180
BMW	83 22 0 136 376
BMW	83 22 2 344 206
BMW	83 22 2 344 207
BMW	83 22 9 407 765
BMW	ATF 4
BMW	ATF 5
BMW	ATF 6
BMW	ETL 7045E
BMW	ETL 8072B
BMW	EZL799/EZL799A
BMW	JWS 3309(T-IV)
BMW	LA 2634
BMW	LT 71141
BMW	ZF 5HP18FL,5HP24,5HP30
BOSCH REXROTH	TE-ML 09
CATERPILLAR	TO-2
CHRYSLER	ATF +,+2, +3
CHRYSLER	Dodge MOPAR AS 68 RC (T-IV) , JWS 3309
CHRYSLER	Dodge/Jeep/ 68043742AA
DAEWOO	LT 71141
DAIHATSU	AMIX CVTF DFC
DAIHATSU	AMIX CVTF DFE
DAIHATSU	AMIX CVTF DTC
DAIHATSU	AMIX CVTF-DC
DAIHATSU	AMMIX ATF D II
DAIHATSU	AMMIX ATF D III SP
DAIHATSU	FLUID TC
DODGE	NS-2/CVTF+4
DTFR	13C140
DTFR	13C150
DTFR	13C170
FIAT	T-IV type
FORD	CVT23
FORD	CVT30
FORD	ESP-M2C166-H
FORD	FRN 5
FORD	MERCON
FORD	MERCON C
FORD	MERCON SP
FORD	WSS-M2C922-A1
FORD	WSS-M2C924-A
FORD	WSS-M2C928-A

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

FORD	WSS-M2C933-A
FORD	XT-2 QSM (Syn)
FORD	XT-2QDX (M)
FORD	XT-6-QSP
FUJIJYUUKO	i-CVTF FG
FUSO	ATF -SP III
FUSO	ATF-A4
FUSO	ATF-II
GEELY	CVTF-EX1
GM	1940700
GM	1940767
GM	21005966
GM	22717466
GM	88863400
GM	88863401
GM	88900925
GM	93160393
GM	9985010
GM	9985835
GM	9986195
GM	AW-1
GM	CVTF GREEN 2/SATURN DEX-CVT
GM	DEXRON II
GM	DEXRON II-D
GM	DEXRON II-E
GM	DEXRON III-G
GM	DEXRON III-H
GM	DEXRON TYPE A, SUFFIX A
GM	HP CVTF 95529854
HINO	Blue Ribon ATF
HONDA	ATF Z-1
HONDA	DW-1
HONDA	HCF-2/HMMF (No Start Clutch)
HONDA	Type 3.0 and 3.1
HONDA	Ultra HEVF-Type 1
HYUNDAI	040000C90SG
HYUNDAI	Dex-II/SP-II
HYUNDAI	SP-CVT1
HYUNDAI	SP-II M
HYUNDAI	SP-III
HYUNDAI	SP-IV M
HYUNDAI	SP-IV M1
ISUZU	08200-9001
ISUZU	BESCO ATF-II
ISUZU	BESCO ATF-III
ISUZU	BESCO ATF-SP
ISUZU	SCS Fluid
JAGUAR	ATF 3403 JLM 20238
JAGUAR	ATF 3403 M115
JAGUAR	JLM 20292
JAGUAR	LT71141 ZF 5HP24
JEEP	ATF +3
JEEP	NS-2/CVTF+4
KIA	SP-CVT 1
LEXUS	JWS 3309
MAZDA	ATF 3317
MAZDA	ATF A7
MAZDA	ATF D-II
MAZDA	ATF F-1
MAZDA	ATF FZ
MAZDA	ATF M-III
MAZDA	ATF M-V (Type M5)
MAZDA	ATF N-1
MAZDA	ATF S-1
MAZDA	CVTF 3320
MB	236.20/CVT28
MB	236.6
MINI	EZL799/EZL799A/CVT V1
MINI	T-IV
MITSUBISHI	CVTF ECO J4
MITSUBISHI	CVTF J-1
MITSUBISHI	CVTF J-4
MITSUBISHI	CVTF J-4+
MITSUBISHI	Diaqueen ATF-PA
MITSUBISHI	Diaqueen AW
MITSUBISHI	Diaqueen J2
MITSUBISHI	Diaqueen J3
MITSUBISHI	Diaqueen SK
MITSUBISHI	Diaqueen SP
MITSUBISHI	Diaqueen SP-II
MITSUBISHI	Diaqueen SP-III
MITSUBISHI	Diaqueen SP-IV
NISSAN	MATIC-C
NISSAN	MATIC-D
NISSAN	MATIC-J
NISSAN	MATIC-K
NISSAN	MATIC-S
NISSAN	NS-1/NS-2/NS-3/Matic W
PORSCHE	000.043.205.09
PORSCHE	000.043.205.28
PORSCHE	999.917.547.00(A2)
PORSCHE	LA 3403-M115
PORSCHE	T-IV (JWS 3309)
PORSCHE	Z 000169756
PSA	1635056080
PSA	9730 AE
PSA	B71 2340
PSA	P/N Z 000169756
PSA	ZF 4HP20
PUNCH	EZL799/EZL799A
RENAULT	CVT CK/SK/FK
RENAULT	DPO/AL4
RENAULT	ELFMATIC
RENAULT	MATIC-D2
RENAULT	Samsung SATF-D
SAAB	93 160 393
SAAB	93 165 147
SAAB	T-IV (JWS 3309)
SCION	(all Vehicles)
SSANG YONG	DSIH 5M-66

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

SUBARU	ATF	TOYOTA	TYPE T-III
SUBARU	ATF 5AT	TOYOTA	TYPE T-IV
SUBARU	ATF, ATF HP	VOLVO	1161521
SUBARU	DEXRON-II	VOLVO	1161540
SUBARU	e-CVTF	VOLVO	1161640
SUBARU	High Torque CVTF	VOLVO	97325
SUBARU	i-CVTF	VOLVO	97335
SUBARU	i-CVTF FG	VOLVO	CE 97340
SUBARU	K0140Y0700	VOLVO	CE 97341
SUBARU	Lineartronic CV-30	VOLVO	CVT 4959
SUBARU	Lineartronic CVTF II	VW	5HP (18FL, 30)
SUZUKI	AT OIL 5D06	VW	5HP (19FL, 24A)
SUZUKI	ATF 2326	VW	5HP (ZF 5 HP 30)
SUZUKI	ATF 2384K	VW	G 052 025
SUZUKI	ATF 3314	VW	G 052 055
SUZUKI	ATF 3317	VW	G 052 162
SUZUKI	ATF AW-1	VW	G 052 180
SUZUKI	ATF JWS 3309	VW	G 052 516
SUZUKI	CVTF 3320	VW	G 052 990
SUZUKI	CVTF 4401	VW	G 053 001
SUZUKI	CVTF GREEN 2	VW	G 053 025
SUZUKI	NS-2/SHELL GREEN 1 V	VW	G 053 162 A1
TOYOTA	ATF D-II	VW	G 055 025
TOYOTA	ATF D-III	VW	G 055 540
TOYOTA	ATF WS	VW	TL 52540-A
TOYOTA	CVT FE	ZF	TE-ML 05L
TOYOTA	TC	ZF	TE-ML 09X
TOYOTA	TYPE T	ZF	TE-ML 21L

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.852
Kinematic viscosity at 40°C	ASTM D445	mm²/s	36.5
Kinematic viscosity at 100°C	ASTM D445	mm²/s	7.5
Viscosity index	ASTM D2270		179
Pour point	ASTM D6892	°C	-51
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	15000
Flash Point COC	ASTM D92	°C	190
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV