WOLF BW FLUID GEN II +

25/09/2026
5096

This fluid is developed for Borg Warner All-Wheel drive coupling applications. It ensures optimum lubrication during the life time of its clutches, with both organic and sinter plates.

APPLICATIONS

This fluid is recommended for all generations of Haldex couplings used in vehicles of the VAG group, Land Rover, and Volvo.

FEATURES

Frictional properties: smooth clutch operation
Anti-wear protection: long clutch life
Applicability: for Haldex clutch system

SPECIFICATIONS

BMW	83 222 413 513	VOLVO	31325136
BMW	HOC	VOLVO	31367940
FORD	FU7J8708687 AA	VOLVO	31367941
GM	93165387	VOLVO	32240904
LAND ROVER	EJ3219A509 AA	VW	G 052 175
LAND ROVER	LR 003136	VW	G 055 175
LAND ROVER	LR 05491	VW	G 060 175
LSC	Fluid SL01-301	VW	G 065 165
LSC	Fluid SL12-301	VW	G 065 175
LSC	Fluid SL99-301	VW	TL 52175-X
MINI	83 22 2 413 513	VW	TL 52175-Y
VOLVO	1161641		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.865
Kinematic viscosity at 40°C	ASTM D445	mm²/s	29.8
Kinematic viscosity at 100°C	ASTM D445	mm²/s	6.23
Viscosity index	ASTM D2270		166
Pour point	ASTM D6892	°C	-51
Copper corrosion (150°C, 3h)	ASTM D130		1A
Flash Point COC	ASTM D92	°C	192

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV