WOLF ECOTECH 75W FE

25/09/2026
2314

This is a full synthetic lubricant based on carefully selected very high quality base oils with low viscosity, used in manual gearboxes of passenger cars, which allows to achieve the highest fuel economy. It offers optimized cold start properties and stable viscosity/temperature behavior.

APPLICATIONS

This product is specifically formulated for gearboxes for which low viscosity manual transmission fluids are recommended.

FEATURES

Anti-wear protection: long transmission life
Frictional properties: very smooth gear shifting, no vibration
Oil life durability: high level of engine cleanliness and durability

SPECIFICATIONS

API	GL-4	PSA	B71 9730 A8
BMW	MTF LT-2	VW	G 052 171
BMW	MTF LT-3	VW	G 052 178
FORD	WSS-M2C200-D2	VW	G 052 512
GM	MTF 0063	VW	G 052 726
NISSAN	LV MTF-1	VW	G 052 798

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.842
Kinematic viscosity at 40°C	ASTM D445	mm^2/s	30.5
Kinematic viscosity at 100°C	ASTM D445	mm^2/s	6.2
Viscosity index	ASTM D2270		157
Pour point	ASTM D6892	°C	-57
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	7000
Flash Point COC	ASTM D92	°C	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV