

WOLF OFFICIALTECH 10W40 UHPD MS

27/09/2023
15708

This is a semi synthetic lubricant based on carefully selected very high quality base oils, which satisfies the highest performance standards for large trucks. It can be used for engines equipped with aftertreatment systems.

APPLICATIONS

Due to its versatile specification levels it is suitable for a wide range of commercial vehicles. Specifically recommended for large truck engines to satisfy the EURO VI standard, TIER IV interim, TIER IV final, TIER V , stage IIIB, stage IV, stage V.

FEATURES

Aftertreatment protection: full after treatment system protection

Total engine protection: outstanding engine cleanliness and durability

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com



PERFORMANCE

ACEA	E11	DEUTZ	DQC IV-10 LA
ACEA	E6-16	DEUTZ	TTCD
ACEA	E7	FORD	WSS-M2C171-F1
ACEA	E8	IVECO	18-1804 Classe T2 E7
ACEA	E9-16	IVECO	18-1804 Classe TLS E9
API	approval CK-4	JD	JDQ-78X
API	CI-4	LIEBHERR	LH-00-ENG5C LA
API	CJ-4	MACK	approval EO-S 4.5
API	SN	MACK	EO-M PLUS
JASO	DH-1	MACK	EO-N
JASO	DH-2	MACK	EO-N Premium Plus
ALLISON	C4	MACK	EO-O Premium Plus
API	approval CI-4 Plus	MAN	approval M3775
CASE	MAT 3571	MAN	M3271-1
CASE	MAT 3572	MAN	M3477
CATERPILLAR	ECF-1a	MAN	M3575
CATERPILLAR	ECF-2	MB	228.31
CATERPILLAR	ECF-3	MB	235.28
CATERPILLAR	TO-2	MB	approval 228.51
CUMMINS	CES 20076	MB	approval 228.52
CUMMINS	CES 20077	MTU	Oil Category 2.1
CUMMINS	CES 20078	MTU	Oil Category 3.1
CUMMINS	CES 20081	RENAULT	approval RLD-3
CUMMINS	CES 20086	RENAULT	RGD
CUMMINS	CES 20092	RENAULT	RLD
DAF	EXTENDED DRAIN	RENAULT	RLD-2
DAIMLER TRUCK	DTFR 13D110	RENAULT	RLD-4
DAIMLER TRUCK	DTFR 15C100	RENAULT	RXD
DAIMLER TRUCK	DTFR 15C110	SCANIA	LA
DAIMLER TRUCK	DTFR 15C120	VOITH	Retarder Oil Class B
DETROIT DIESEL	DFS 93K215	VOLVO	approval VDS-4.5
DETROIT DIESEL	DFS 93K218	VOLVO	VDS-3
DETROIT DIESEL	DFS 93K222	VOLVO	VDS-4
DEUTZ	approval DQC-IV-18 LA		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.858
Kinematic viscosity at 40°C	ASTM D445	mm²/s	89.9
Kinematic viscosity at 100°C	ASTM D445	mm²/s	13.9
Viscosity index	ASTM D2270		158
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	10.2
Pour point	ASTM D6892	°C	-33
CCS viscosity at -25°C	ASTM D5293	mPa.s	6600
Flash Point COC	ASTM D92	°C	216

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com

