WOLF EXTENDTECH 85W140 LS GL 5

25/09/2026
2409

Mineral oil composed of paraffinic base oils and selected additives based on sulfur-phosphorus. A special friction additive emparts to this oil the necessary properties to be used in differentials, which are equipped with a "limited-slip" mechanism.

APPLICATIONS

This oil is mainly used in all hypoid rear axles with a limited-slip mechanism.

FEATURES

Frictional properties: easy gear shifting
Anti-wear protection: long transmission life

SPECIFICATIONS

API	GL-5	ZF	TE-ML 07A
MIL	L-2105 C	ZF	TE-ML 08
MIL	L-2105 D		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.905
Kinematic viscosity at 40°C	ASTM D445	mm²/s	415
Kinematic viscosity at 100°C	ASTM D445	mm²/s	26.5
Viscosity index	ASTM D2270		86
Pour point	ASTM D6892	°C	-18
Brookfield viscosity at -12°C	ASTM D2983	mPa.s	100000
Flash Point COC	ASTM D92	°C	215

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV