WOLF OE LEVELTECH 5W-30 UHPD

25/09/2026
75707

This synthetic based engine oil meets the specifications of a very broad range of different large truck manufacturers. Its low viscosity formulation and advanced friction modifiers allow you to increase fuel efficiency.

APPLICATIONS

This versatile lubricant can be used in a broad range of different EURO V and EURO VI engines. It meets the specifications of different off- and on-road engine manufacturers, such as: Caterpillar, Cummins, DAF, Daimler Truck, Iveco, MAN, Renault, Scania, Volvo, etc.

FEATURES

Viscosity and friction: the purpose is low friction and low viscosity
Broad applicability: can be used to service multiple vehicles within one fleet

SPECIFICATIONS

ACEA	E11	IVECO	18-1804 Classe TLS E9
ACEA	E6-16	MACK	EO-M PLUS
ACEA	E7	MACK	EO-N
ACEA	E8	MACK	EO-N Premium Plus
ACEA	E9-16	MACK	EO-O Premium Plus
API	CI-4	MACK	EO-S 4.5
API	CJ-4	MAN	M3271-1
API	CK-4	MAN	M3277
API	SN	MAN	M3477
JASO	DH-2	MAN	M3575
CATERPILLAR	ECF-3	MAN	M3677
CUMMINS	CES 20077	MAN	M3775
CUMMINS	CES 20081	MB	235.28
CUMMINS	CES 20086	MTU	Oil Category 2.1
DAF	EXTENDED DRAIN	MTU	Oil Category 3
DAF	PSQL 2.1 E	MTU	Oil Category 3.1
DAF	PSQL 2.1 E LD	RENAULT	RGD
DETROIT DIESEL	DFS 93K218	RENAULT	RLD
DETROIT DIESEL	DFS 93K222	RENAULT	RLD-2
DEUTZ	DQC IV-10 LA	RENAULT	RLD-3
DEUTZ	DQC-IV-10	RENAULT	RLD-4
DEUTZ	DQC-IV-18 LA	RENAULT	RXD
DEUTZ	TTCD	SCANIA	LDF-3 (excl. V8 engines)
DTFR	13D110	SCANIA	LDF-4
DTFR	15C100	VOITH	Retarder Oil Class B
DTFR	15C110	VOLVO	VDS-3
DTFR	15C120	VOLVO	VDS-4
FORD	WSS-M2C213-A1	VOLVO	VDS-4.5

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.855
Kinematic viscosity at 40°C	ASTM D445	mm^2/s	74.6
Kinematic viscosity at 100°C	ASTM D445	mm^2/s	12.2
Viscosity index	ASTM D2270		161
B.N. (HCLO4 method)	ASTM D2896	mg KOH/g	11.9
Pour point	ASTM D6892	°C	-39
Sulfated Ash	ASTM D874	Mass %	0.99
Flash Point COC	ASTM D92	°C	222

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV