WOLF ESSENTIAL
ATF DEXRON III

25/09/2026
75952

This ATF fluid has a high viscosity index to ensure great fluidity on engine start and guaranteed component protection at high temperatures.

APPLICATIONS

Can be used to service a range of different automatic transmission systems, torque convertors, power steering systems and hydraulic circuits.

FEATURES

Frictional properties: smooth shift performance
Anti-wear protection: long transmission life

SPECIFICATIONS

ALLISON	C4	FORD	ESP-M2C166-H
CATERPILLAR	TO-2	FORD	MERCON
DTFR	13C120	GM	DEXRON III-H
FORD	ESP-M2C138-CJ		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.849
Kinematic viscosity at 40°C	ASTM D445	mm^2/s	32.0
Kinematic viscosity at 100°C	ASTM D445	mm^2/s	6.82
Viscosity index	ASTM D2270		181
Pour point	ASTM D6892	°C	-51
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	14140
Flash Point COC	ASTM D92	°C	198
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV