

0W-40 A3/B4 Pro

Description:

0W-40 A3/B4 Pro is a fully synthetic low friction engine oil with excellent suitability for all modern PC gasoline and diesel engines. It meets most severe requirements of leading manufacturers of vehicles, and it is especially advisable for multivalve arrangement, turbocharger and direct injection (DI).

Because of its extreme viscosity range **0W-40 A3/B4 Pro** provides for smooth cold start, and even at high temperatures it rapidly forms a coherent oil film on critical engine parts. Being formulated with high-quality additives the oil protects optimal against wear and its outstanding dispersant- and detergent characteristics prevent deposit formation in the engine.

Properties:

0W-40 A3/B4 Pro stands for extreme shear stability and high oxidation resistance. Due to the synthetic base oil there is only few volatility loss.

0W-40 A3/B4 Pro represents by its total benefits a high-quality product of remarkable economy. Extended engine life, less maintenance-costs, reduced oil and fuel consumption are strong demonstration.

Specification / Recommendations:

ACEA A3-/B4-12

API SN/CF

VW 502 00 / 505 00

Renault RN 0700 / 0710

MB 229.5

BMW Longlife-01

Porsche A40

Ford WSS-M2C937-A

Typical Values:

0W-40 A3/B4 Pro	Unit	Value	Method
Density at 15°C	kg/m ³	845	DIN 51 757
Viscosity at 40°C	mm ² /s	74,8	DIN 51 562
Viscosity at 100°C	mm ² /s	13,4	DIN 51 562
Viscosity Index		185	DIN ISO 2909
CCS at -35°C	mPa.s	6120	DIN 51 377
Pourpoint	°C	-54	DIN ISO 3016
Flashpoint	°C	235	DIN ISO 2592
TBN	mg KOH/g	10,2	DIN ISO 3771

*Specification variations in these characteristics may occur. The instructions of manufacturer must be regarded.
Further information available by MSDS.*

Hengst SE

Nienkamp 55-85

48147 Münster

Germany

Tel.: +49 251 20202-0

