# WOLF ECOTECH
# MULTI VEHICLE ATF FE

25/09/2026
3014

This is a full synthetic lubricant based on carefull selected very highly refined base oils for automatic transmissions with a high viscosity index, excellent oxidation stability, excellent friction and anti-wear properties providing excellent fuel economy and meeting the requirements of most American, Japanese and European manufacturers.

## APPLICATIONS

Its versatile nature guarantees it can be used in the latest generations of automatic transmissions and torque convertors for most passenger cars, off-road vehicles and SUVs.

## FEATURES

Frictional properties: very smooth gear shifting, no vibration
Anti-wear protection: long transmission life
Oil life durability: high level of thermal and oxidation stability

## SPECIFICATIONS

| | | | |
|---|---|---|---|
| AISIN-WARNER | AW-1 | HONDA | DPSF2 |
| AISIN-WARNER | AW-2 | HONDA | DW-1 |
| AISIN-WARNER | JWS 3324 | HYUNDAI | NWS-9638 T5 |
| ALLISON | C4 | HYUNDAI | SPH-IV |
| BMW | 000 043 306 24 | HYUNDAI | SP-IV |
| BMW | 83 22 0 397 114 | ISUZU | WSI |
| BMW | 83 22 2 305 397 | JAGUAR | 02JDE26444 |
| BMW | 83 22 9 407 858 | LAND ROVER | LR023288 |
| BMW | 83222152426 | MAZDA | FZ |
| BMW | 83222167718 | MB | 236.12 |
| BMW | 83222413477 | MB | 236.14 |
| BMW | 958 300 540 00 | MB | 236.41 |
| BMW | ATF 3 | MITSUBISHI | ATF J3 |
| BMW | ATF 6 | MITSUBISHI | Diaqueen ATF-PA |
| BMW | ATF 7 | NISSAN | MATIC-S |
| BMW | L 12108 | PSA | 1635056080 |
| BMW | M-1375.4 | TESLA | ATF9/EDF2 |
| CHRYSLER | 68157995AA | TOYOTA | AUTO FLUID WS |
| FIAT | 9.55550-AV2 | VOLVO | 31256774 |
| FIAT | 9.55550-AV5 | VOLVO | 31256775 |
| FORD | MERCON LV | VOLVO | 31256776 |
| FORD | MERCON SP | VOLVO | 31492172 |
| FORD | WSS-M2C195-A | VOLVO | 31492173 |
| FORD | WSS-M2C924-A | VW | G 053 001 |
| FORD | WSS-M2C938-A | VW | G 055 005 |
| GM | DEXRON HP | VW | G 055 162 |
| GM | DEXRON VI | VW | G 055 540 |
| HONDA | DPSF | VW | G 060 162 |

**WOLF OIL CORPORATION NV**
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com



The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

## TYPICAL CHARACTERISTICS

| Test | Method | Unit | Average results |
|---|---|---|---|
| Density at 15°C | ASTM D4052 | g/ml | 0.851 |
| Kinematic viscosity at 40°C | ASTM D445 | $mm^2/s$ | 32.5 |
| Kinematic viscosity at 100°C | ASTM D445 | $mm^2/s$ | 6.45 |
| Viscosity index | ASTM D2270 | | 156 |
| Pour point | ASTM D6892 | °C | -45 |
| Brookfield viscosity at -40°C | ASTM D2983 | mPa.s | <=20000 |
| Flash Point COC | ASTM D92 | °C | 210 |
| Colour | VISUAL | | RED |

**We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.**

**WOLF OIL CORPORATION NV**
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com



The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV