

WOLF OFFICIALTECH 10W40 UHPD EXTRA

04/09/2023
65636

The state of the art wear-reducing additives contained within this synthetic engine oil are engineered to combine stable oil performance with excellent engine protection, resulting in extended drain intervals. The protective oil film retains its excellent properties over a wide range of temperatures. Furthermore, the engine oil has high shear resistance, cutting down on maintenance costs by further extending drain intervals.

APPLICATIONS

Both off- and on-road heavy-duty applications with or without turbochargers, superchargers or after-treatment systems can be serviced with this engine oil. It meets the specifications of a wide range of high-demanding specifications including the Volvo VDS-4.5. Thanks to its backward compatibility, this versatile engine oil can be used in both modern and older engines. It is compatible with emission control technology EURO IV, V and VI.

FEATURES

Aftertreatment protection: full aftertreatment system protection.
Total engine protection: outstanding engine cleanliness and durability.
Fuel economy: lower fuel consumption and CO2 emissions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com



PERFORMANCE

ACEA	E11	DEUTZ	TTCO
ACEA	E4	FORD	WSS-M2C171-F1
ACEA	E6-16	IVECO	18-1804 Classe T2 E7
ACEA	E7	IVECO	18-1804 Classe TLS E6
ACEA	E8	IVECO	18-1804 Classe TLS E9
ACEA	E9-16	IVECO	18-1809 Classe NG2
API	CI-4	JD	JDQ-78X
API	CJ-4	LIEBHERR	LH-00-ENG5C LA
API	CK-4	MACK	approval EO-S 4.5
API	SN	MACK	EO-M PLUS
JASO	DH-1	MACK	EO-N
JASO	DH-2-17	MACK	EO-N Premium Plus
ALLISON	C4	MACK	EO-O Premium Plus
API	CI-4 Plus	MAN	M3271-1
CASE	MAT 3571	MAN	M3477
CASE	MAT 3572	MAN	M3575
CATERPILLAR	ECF-1a	MAN	M3775
CATERPILLAR	ECF-2	MB	228.31
CATERPILLAR	ECF-3	MB	235.28
CATERPILLAR	TO-2	MB	approval 228.51
CUMMINS	CES 20076	MB	approval 228.52
CUMMINS	CES 20077	MTU	approval Oil Category 3.1
CUMMINS	CES 20078	MTU	Oil Category 2.1
CUMMINS	CES 20081	RENAULT	approval RLD-3
CUMMINS	CES 20086	RENAULT	RGD
DAF	EXTENDED DRAIN	RENAULT	RLD
DAIMLER TRUCK	DTFR 13D110	RENAULT	RLD-2
DAIMLER TRUCK	DTFR 15C100	RENAULT	RLD-4
DAIMLER TRUCK	DTFR 15C110	RENAULT	RXD
DAIMLER TRUCK	DTFR 15C120	SCANIA	LA
DETROIT DIESEL	DFS 93K215	VOITH	Retarder Oil Class B
DETROIT DIESEL	DFS 93K218	VOLVO	approval VDS-4.5
DETROIT DIESEL	DFS 93K222	VOLVO	VDS-3
DEUTZ	approval DQC-IV-18 LA	VOLVO	VDS-4
DEUTZ	DQC IV-10 LA		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.859
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	86.0
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	13.3
Viscosity index	ASTM D2270		156
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	13.4
Pour point	ASTM D6892	°C	-36
Flash Point COC	ASTM D92	°C	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

