WOLF OFFICIALTECH
ATF LIFE PROTECT 6

25/09/2026
3012

This is a full synthetic lubricant based on carefully selected very high quality base oils that has been specifically developed for ZF 6-speed automatic transmissions. Its particular formulation ensures a trouble-free operation and smooth gear shifting.

APPLICATIONS

Mainly intended for the ZF-6 speed automatic transmissions, as fitted in BMW, Jaguar and Land Rover, it is also suitable for other OEMs, who recommend this type of fluid (e.g. Audi Quattro).

FEATURES

Anti-wear protection: long transmission life
Frictional properties: very smooth gear shifting, no vibration
Oil life durability: high level of thermal and oxidation stability

SPECIFICATIONS

AML	4G4319A509/AA/S	HYUNDAI	040000C90SG
BENTLEY	PY112995PA	JAGUAR	Fluid 8432
BMW	83 22 2 305 396	LAND ROVER	TYK500050
BMW	83220142516	MASERATI	231603
BMW	ATF 2	VW	G 055 005
BMW	M-1375.4	ZF	TE-ML 11

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.850
Kinematic viscosity at 40°C	ASTM D445	mm^2/s	31.0
Kinematic viscosity at 100°C	ASTM D445	mm^2/s	6.17
Viscosity index	ASTM D2270		152
Pour point	ASTM D6892	°C	-48
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	<=20000
Flash Point COC	ASTM D92	°C	202
Colour	VISUAL		AMBER

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV