

Anziehvorschrift für Zylinderkopf		535.640		 Das Original																				
Tightening Instructions for Cylinder Head		passend für / suitable for adaptable à / adaptable a																						
Instructions de serrage pour culasse																								
Prescripciones de apriete para culatas		Mercedes-Benz																						
Schraubenkopf / Head shape Tête de vis / Cabeza de tornillo		Anziehreihenfolge/Tightening sequence/Ordre de serrage/Orden de apriete																						
		<table border="1"><tr><td>9</td><td>5</td><td>1</td><td>4</td><td>8</td></tr><tr><td>10</td><td>6</td><td>2</td><td>3</td><td>7</td></tr><tr><td>10</td><td>6</td><td>2</td><td>3</td><td>7</td></tr><tr><td>9</td><td>5</td><td>1</td><td>4</td><td>8</td></tr></table>			9	5	1	4	8	10	6	2	3	7	10	6	2	3	7	9	5	1	4	8
9	5	1	4	8																				
10	6	2	3	7																				
10	6	2	3	7																				
9	5	1	4	8																				
535.860 M 11x1,5x170																								
Anziehen/ Tightening/ Serrage/ Apriete		M11 * 20 Nm 40 Nm ➤ 90° ➤ 90°		M8 15 Nm ➤ 90°																				
Zeichenerklärung / Explanations / Explication / Explicacion																								
✱	neue Zylinderkopf-schrauben verwenden	use new cylinder head bolts	utiliser des vis neuves	emplar tornillos nuevos																				
★	Warmlauf (80°C)	warm up time (80°C)	chauffage (80°C)	calentamiento (80°C)																				
☐	Schrauben einzeln lösen und wieder anziehen	loosen and tighten each bolt	deserrer et serrer vis par vis	aflojar y apretar tornillo a tornillo																				
●	Setzzeit	relaxation time	durée de tassement	tiempo de espera																				
➤	Drehwinkel	torque angle	angle de serrage	ángulo de giro																				
Motortyp / Engine type / Type de moteur / Tipo de motor																								
Ø 93,4 mm; ± 1,1 mm																								
Mot: M 273.923																								
S 450 W221 GL 450 X164																								
rechts/right/droit/derecha/destra																								
ElringKlinger AG, Max-Eyth-Str.2 72581 Dettingen / Erms. Tel. 07123/724 601			*535.640*																					