


Anziehvorschrift für Zylinderkopf		287.560	 Das Original
Tightening Instructions for Cylinder Head		passend für / suitable for	
Instructions de serrage pour culasse		adaptable à / adaptable a	
Prescripciones de apriete para culatas		Ford/Volvo	
Schraubenkopf / Head shape Tête de vis / Cabeza de tornillo		Anziehreihenfolge/Tightening sequence/Ordre de serrage/Orden de apriete	
 087.830 M 10x1,5x143			
Anziehen/ Tightening/ Serrage/ Apriete	* ➤	15 Nm 30 Nm 90°	
Zeichenerklärung / Explanations / Explication / Explicacion			
* ★ □ ● ➤	neue Zylinderkopf- schrauben verwenden Warmlauf (80°C) Schrauben einzeln lösen und wieder anziehen Setzzeit Drehwinkel	use new cylinder head bolts warm up time (80°C) loosen and tighten each bolt relaxation time torque angle	utiliser des vis neuves chauffage (80°C) deserrer et serrer vis par vis durée de tassement angle de serrage emplar tornillos nuevos calentamiento (80°C) aflojar y apretar tornillo a tornillo tiempo de espera ángulo de giro
Motortyp / Engine type / Type de moteur / Tipo de motor			
Ø: 79,8 mm; $\frac{1}{2}$: 0,32 mm			
Mot: FYJA; FYJB; SHDA; HWDB; HWDA 1,6 Ltr. 74 KW (100 PS)			
Fiesta V, Fusion ➔ 11.2008 Focus, Focus C-Max ➔ 03.2007			
ElringKlinger AG, Max-Eyth-Str.2 72581 Dettingen / Erms. Tel. 07123/724 601		*287.560*	