WOLF OFFICIALTECH
0W-20 C5 P

25/09/2026
65657

A low SAPS ACEA C5 passenger car engine oil focused on the most recent Stellantis / PSA specification B71 2010, but also suitable for diesel and gasoline engines from other car manufacturers which require an ACEA C5 SAE 0W-20 oil.

APPLICATIONS

Specifically designed for the most recent PSA GROUP (Peugeot/Citroën/DS) engines which require a PSA B71 2010 oil as Blue HDi, PureTech, hybrid engines, engines equipped with a Stop & Start system, etc. This ACEA C5 oil is also suitable for diesel and gasoline engines from other car manufacturers which require an ACEA C5 SAE 0W-20 oil.

FEATURES

Aftertreatment protection: the purpose is full aftertreatment device protection
Cold start: high level of fluidity at low temperature
Fuel economy: the purpose is good fuel economy and low exhaust emissions

SPECIFICATIONS

ACEA	C5
API	SN Plus
API	SP
ILSAC	GF-5
ILSAC	GF-6A
CHRYSLER	MS 6395
FIAT	9.55535-CR1
FIAT	9.55535-DM1
FIAT	9.55535-DSX
FIAT	9.55535-GSX
HONDA	SFU
HYUNDAI	SFU
INFINITI	SFU
KIA	SFU
LEXUS	SFU
MAZDA	SFU
MB	229.71
NISSAN	SFU
OPEL	OV 040 1547 - A20
PERODUA	SFU
PSA	B71 2010-22
ROEWE	SFU
SCION	SFU
SUBARU	SFU
TATA	SFU
TIANJIN	SFU
TOYOTA	SFU

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.845
Kinematic viscosity at 40°C	ASTM D445	mm^2/s	43.5
Kinematic viscosity at 100°C	ASTM D445	mm^2/s	8.3
Viscosity index	ASTM D2270		170
Pour point	ASTM D6892	°C	-48
Flash Point COC	ASTM D92	°C	232

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV