# WOLF COOLANT
# ASIAN LL -36°C

25/09/2026
50155

High-performing ready-to-use coolant based on ethylene glycol with state-of-the-art P-OAT corrosion protection technology, for modern high performance engines. With the P-OAT technology, organic acids work together with with mineral inhibitors for the best possible protection.

## APPLICATIONS

This P-OAT coolant is especially developed for the protection of modern combustion engines cooling systems present in Asian OEM's.
It is basically miscible with most OAT MEG based coolants but for the best possible corrosion protection we recommend to use only this P-OAT coolant for long-term protection.

## FEATURES

System protection: high level of heat transfer and dispersion
Anti-corrosion properties: high level of corrosion protection
Anti-freeze properties: high level of cold temperature performance

## SPECIFICATIONS

| | | | |
|---|---|---|---|
| ASTM | D3306 | MAZDA | C100CL005A4X |
| ASTM | D6210 | MAZDA | C122CL005A4X |
| JIS | K2234:2018 | MAZDA | FL 22 |
| FORD | VC-10-A2 | MITSUBISHI | Diaqueen Super LL Coolant |
| FORD | WSS-M97B55 | NISSAN | ANTI-FREEZE COOLANT (L250) |
| HONDA | 08CLA010S0 Honda E Coolant | NISSAN | KE90299934 |
| HONDA | TYPE 2 | NISSAN | KE90299944 |
| HYUNDAI | 00232-19010 | NISSAN | L255N |
| HYUNDAI | 07100-00200 | RENAULT | RX TYPE E COOLANT |
| HYUNDAI | 07100-00400 | SUBARU | Coolant 16218 |
| HYUNDAI | Long Life Coolant | SUZUKI | (SUPER) LL COOLANT |
| LEXUS | SFU | TOYOTA | TSK 2601G-8A |
| MAZDA | 000077508E20 | | |

## TYPICAL CHARACTERISTICS

| Test | Method | Unit | Average results |
|---|---|---|---|
| pH | ASTM D1287 | | 8.3 |
| Density at 20°C | ASTM D4052 | g/ml | 1,074 |
| Colour | VISUAL | | GREEN / DARK |
| Freezing point (refracto) | ASTM D3321 | °C | -36 |
| Water content | ASTM D1123 | % wt/wt | 50 |

**We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.**

**WOLF OIL CORPORATION NV**
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com



The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV