WOLF OFFICIALTECH
0W20 LL FE

25/09/2026
65621

This is a full synthetic lubricant mandatory for the newest engines of VW/Audi. It is developed to prolong the life and maintain the efficiency of emission systems. It is also designed to provide outstanding engine cleanliness, wear protection and strong durability to keep your engine running like new. A substantial fuel saving is reached through the use of the ultra low 0W20 viscosity grade.

APPLICATIONS

This product is developed for mandatory use in the newest 2.0 TFSI 140 kW and 3.0 TDI CR 160 kW engines of VW and Audi which require the VW specification 508 00 and 509 00.

FEATURES

Engine protection: ensures high level of the engine cleanliness
Fuel economy: the purpose is good fuel economy and low exhaust emissions
Cold start: high level of fluidity at low temperature

SPECIFICATIONS

ACEA	C5	BYD	SFU
ACEA	C6	FORD	WSS-M2C956-A1
API	approval SN Plus	PORSCHE	approval C20
API	SP	VW	approval 508 00/509 00
API	SP/RC	VW	TL 52 577
ILSAC	GF-6A		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.843
Kinematic viscosity at 40°C	ASTM D445	mm²/s	40.2
Kinematic viscosity at 100°C	ASTM D445	mm²/s	8.2
Viscosity index	ASTM D2270		184
B.N. (HCLO4 method)	ASTM D2896	mg KOH/g	8.3
Pour point	ASTM D6892	°C	-45
Sulfated Ash	ASTM D874	Mass %	0.79
Flash Point COC	ASTM D92	°C	235
Colour	VISUAL		GREEN
CCS viscosity at -35°C	ASTM D5293	mPa.s	3500

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV