WOLF VITALTECH
MULTI VEHICLE ATF

25/09/2026
3010

This is a full synthetic lubricant based on carefully selected very highly refined base oils for automatic transmissions , meeting the requirements of most American, Japanese and European manufacturers.

APPLICATIONS

Its versatile nature guarantees it can be used in automatic transmissions and torque convertors for most passenger cars, off-road vehicles and SUVs.

FEATURES

Frictional properties: very smooth gear shifting, no vibration
Anti-wear protection: long transmission life
Oil life durability: high level of thermal and oxidation stability

SPECIFICATIONS

IDEMITSU	K17	CHRYSLER	05127382AA
JASO	M315, Class 1A	CHRYSLER	AS68RC ATF
AISIN-WARNER	AW-1	CHRYSLER	ATF +3 AND +4
AISIN-WARNER	JWS 3309	CHRYSLER	MD 7176E
AISIN-WARNER	JWS 3314	CHRYSLER	MS 9602
AISIN-WARNER	JWS 3317	DTFR	13C100
ALFA ROMEO	HP20	DTFR	13C110
ALLISON	C4	DTFR	13C120
ALLISON	TES 295	DTFR	13C140
ALLISON	TES 389	DTFR	13C150
BENTLEY	PY112995PA	DTFR	13C170
BMW	81 22 9 400 275	DTFR	13C180
BMW	81 22 9 401 220	DTFR	38B100
BMW	83 22 0 024 359	FIAT	9.55550-AV1
BMW	83 22 0 026 922	FIAT	9.55550-AV4
BMW	83 22 0 142 516	FORD	ESP-M2C138-CJ
BMW	83 22 0 403 248	FORD	ESP-M2C166-H
BMW	83 22 0 403 249	FORD	M2C-138CJ, Mercon
BMW	83 22 2 152 426	FORD	M2C-202B
BMW	83 22 2 344 206	FORD	MERCON
BMW	83 22 2 355 599	FORD	MERCON V
BMW	83 22 9 407 765	FORD	WSS-M2C195-A
BMW	83 22 9 407 807	FORD	WSS-M2C919-E
BMW	ATF 3	FORD	WSS-M2C922-A1
BMW	ATF 4	FORD	WSS-M2C924-A
BMW	ATF 6	GM	1940700
BMW	ETL 7045E	GM	1940767
BMW	ETL 8072B	GM	210005966
BMW	LA 2634	GM	22717466
BMW	LT 71141	GM	6032-M DEXRON
BMW	ZF 5HP18FL,5HP24,5HP30	GM	88900925

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

GM	9986195
GM	DEXRON II
GM	DEXRON II-D
GM	DEXRON II-E
GM	DEXRON III
GM	DEXRON III-G
GM	DEXRON III-H
GM	DEXRON TYPE A, SUFFIX A
HONDA	ATF Z-1
HONDA	Premium
HYUNDAI	SFU
HYUNDAI	SP-II
HYUNDAI	SP-III
ISUZU	BESCO ATF-II
ISUZU	BESCO ATF-III
ISUZU	Genuine
ISUZU	PSF
ISUZU	SCS Fluid
JAGUAR	ATF 3403 M115
JAGUAR	Fluid 8432
JAGUAR	JLM 20238
JAGUAR	JLM 20292 (LA 3403-M115)
JAGUAR	JLM 21044
JEEP	ATF 3
KIA	ATF Red -1K
KIA	SP-II
KIA	SP-III
LAND ROVER	LR002748
LAND ROVER	N402
LEXUS	TYPE T-IV
MAN	339 V1/Z1
MAN	339 V2/Z2
MAN	339 Z3
MASERATI	231603
MAZDA	ATF 3317
MAZDA	ATF D-II
MAZDA	ATF F-1
MAZDA	ATF FZ
MAZDA	ATF M-III
MAZDA	ATF M-V (Type M5)
MAZDA	ATF N-1
MAZDA	ATF S-1
MB	236.1
MB	236.10
MB	236.11
MB	236.12
MB	236.14
MB	236.2
MB	236.3
MB	236.5
MB	236.6
MB	236.7
MB	236.8
MB	236.9
MB	236.91
MINI	83 0 402 42
MINI	T-IV
MITSUBISHI	4030401
MITSUBISHI	ATF J2
MITSUBISHI	Diaqueen ATF MA1
MITSUBISHI	Diaqueen ATF-PA
MITSUBISHI	Diaqueen J3
MITSUBISHI	Diaqueen SK
MITSUBISHI	Diaqueen SP-II
MITSUBISHI	Diaqueen SP-III
MITSUBISHI	Diaqueen SP-IV
MITSUBISHI	SFU
MITSUBISHI	V5AWF
MOPAR	ATF +3
MOPAR	ATF +4
NISSAN	999MP-ATFD3MP
NISSAN	D3m
NISSAN	MATIC-D
NISSAN	MATIC-J
NISSAN	MATIC-K
NISSAN	MATIC-W
OPEL	GM 1940700
OPEL	GM 1940767
OPEL	GM 21005966 Transaxle
OPEL	GM 2217466
OPEL	GM 9986185
PORSCHE	000.043.202.28
PORSCHE	000.043.204.63
PORSCHE	000.043.205.09
PORSCHE	000.043.207.00
PORSCHE	000.43.305.43
PORSCHE	999.917.547.00(A2)
PORSCHE	JWS 3309 (Cayenne)
PORSCHE	LA 3403-M115
PORSCHE	T-IV (JWS 3309)
PSA	P/N Z 000169756
PSA	ZF 4HP20
RENAULT	A14
RENAULT	DPO/AL4
RENAULT	MATIC-D2
RENAULT	Samsung SATF-D
SAAB	T-IV (JWS 3309)
SAAB	Transmax J- TIV
SCION	T-II
SCION	T-III
SCION	T-IV
SUBARU	ATF 5AT
SUBARU	ATF, ATF HP
SUBARU	K0140Y0700
SUZUKI	AT OIL 5D06
SUZUKI	ATF 2324K
SUZUKI	ATF 2326
SUZUKI	ATF 3310
SUZUKI	ATF 3311
SUZUKI	ATF JWS 3309

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

SUZUKI	Dexron III	VW	G 055 540
TOYOTA	TYPE T-II	VW	G 060 162
TOYOTA	TYPE T-III	VW	G US 000 162
TOYOTA	TYPE T-IV	VW	TL 52 162
VOITH	55.6335(G607. G1363)	VW	TL 5612
VOITH	DIWA #013S	ZF	TE-ML 02F
VOLVO Constr. Equip. (VCE)	1273,41	ZF	TE-ML 03D
VOLVO	1161540	ZF	TE-ML 04D
VOLVO	97325	ZF	TE-ML 09
VOLVO	CE 97340	ZF	TE-ML 11A
VOLVO	JWS 3309	ZF	TE-ML 11B
VW	G 052 025	ZF	TE-ML 14A
VW	G 052 055	ZF	TE-ML 14B
VW	G 052 162	ZF	TE-ML 14C
VW	G 052 533	ZF	TE-ML 16L
VW	G 052 990	ZF	TE-ML 17C
VW	G 055 025		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.851
Kinematic viscosity at 40°C	ASTM D445	mm^2/s	36.3
Kinematic viscosity at 100°C	ASTM D445	mm^2/s	6.84
Viscosity index	ASTM D2270		150
Pour point	ASTM D6892	°C	-48
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	<=20000
Flash Point COC	ASTM D92	°C	218
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com