WOLF OFFICIALTECH
5W-30 MS-GD

25/09/2026
65665

This synthetic engine oil guarantees a cleaner and better performing engine without lowering the oil drain interval.
It is based on carefully selected very high quality base oils and formulated using the latest technology for catalyst compatible engine oils.
The broad applicability of this engine oil enables you to offer perfect maintenance to different vehicles of several major brands.

APPLICATIONS

This engine oil can be used in systems with or without exhaust gas aftertreatment where C2 (PSA) or C3 (German OEM's) engine oils are required.
Furthermore, this engine oil has an official GM dexosD approval. DexosD meets or exceeds the performance of dexos2 and is backward compatible.

FEATURES

Aftertreatment protection: the purpose is full aftertreatment device protection
Fuel economy: the purpose is great fuel economy and lower exhaust emissions
Engine protection: high level of engine cleanliness and durability

SPECIFICATIONS

ACEA	C2	VW	502 00 < 2017
ACEA	C3	VW	505 00
API	CF	VW	505 01
API	SN		
API	SP		
BMW	LONGLIFE-04		
CHRYSLER	MS 11106		
FIAT	9.55535-S3		
FORD	WSS-M2C917-A		
GM	approval dexos™2		
GM	approval dexos™D		
GM	dexos™1 Gen 3		
HYUNDAI	SFU		
KIA	SFU		
MB	226.5		
MB	229.31		
MB	229.51		
MB	229.52		
OPEL	GM-LL-A-025		
OPEL	GM-LL-B-025		
OPEL	OV 040 1547 - D30		
OPEL	OV 040 1547 - G30		
RENAULT	RN 0700		
RENAULT	RN 0710		

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.852
Kinematic viscosity at 40°C	ASTM D445	mm^2/s	75.56
Kinematic viscosity at 100°C	ASTM D445	mm^2/s	12.4
Viscosity index	ASTM D2270		163
B.N. (HCLO4 method)	ASTM D2896	mg KOH/g	8.0
Pour point	ASTM D6892	°C	-39
Flash Point COC	ASTM D92	°C	230

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV