WOLF OFFICIALTECH
5W-30 MS-SFE

25/09/2026
65663

A low SAPS ACEA C3 passenger car engine oil focused on the most recent Stellantis specification FPW9.55535/03 and on the PSA specifications B71 2290 and B71 2297 (for hot climates).
Also suitable for diesel and gasoline engines from other car manufacturers which require an ACEA C3 SAE 5W-30 oil.

APPLICATIONS

Developed for a wide range of passenger cars, SUVs and light vans. It is designed for modern high efficiency gasoline, diesel and hybrid cars from Stellantis (PSA, Opel, Vauxhall), MB and GM, as well as for Asian vehicles that specifically require a SAE 5W-30 oil specification.

FEATURES

Aftertreatment protection: the purpose is full aftertreatment device protection
Cold start: high level of fluidity at low temperature
Fuel economy: the purpose is good fuel economy and low exhaust emissions

SPECIFICATIONS

ACEA	C3	MB	229.51
API	SN Plus	MB	229.52
API	SP	OPEL	OV 040 1547 - D30
API	SQ	OPEL	OV 040 1547 - G30
CHINESE STANDARD	GB 11121	PSA	B71 2290
GM	dexos™2	PSA	B71 2297
MB	229.31	STELLANTIS	FPW9.55535/03

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.847
Kinematic viscosity at 40°C	ASTM D445	mm²/s	66.1
Kinematic viscosity at 100°C	ASTM D445	mm²/s	11.5
Viscosity index	ASTM D2270		170
Pour point	ASTM D6892	°C	-42
Flash Point COC	ASTM D92	°C	254

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV