WOLF OFFICIALTECH 5W30 FS-M

25/09/2026
65625

A synthetic lubricant for the newest Mercedes-Benz AMG engines requiring a full SAPS engine oil with an official MB 229.6 approval. The low viscosity grade enables the engine to run at high fuel-efficiency. This engine oil optimizes wear protection and engine cleanliness.

APPLICATIONS

The official MB 229.6 approval indicates that this full SAPS engine oil is especially formulated for the latest Mercedes-Benz AMG high performance engines. Furthermore it can be used in all engines requiring ACEA A5/B5 engine oils.

FEATURES

Fuel economy: the purpose is good fuel economy and low exhaust emissions

SPECIFICATIONS

ACEA	A1/B1-12	API	SL
ACEA	A5/B5	MB	229.6

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.852
Kinematic viscosity at 40°C	ASTM D445	mm²/s	59.4
Kinematic viscosity at 100°C	ASTM D445	mm²/s	10.3
Viscosity index	ASTM D2270		162
B.N. (HCLO4 method)	ASTM D2896	mg KOH/g	10.1
Pour point	ASTM D6892	°C	-48
Sulfated Ash	ASTM D874	Mass %	1.1
Flash Point COC	ASTM D92	°C	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV