WOLF OFFICIALTECH
0W-20 FXFE

25/09/2026
65662

A low SAPS passenger car engine oil focused on the most Ford engine oil specification WSS-M2C954-A1.

APPLICATIONS

Especially developed for Ford engines where Ford WSS-M2C954-A1 is required.

FEATURES

Aftertreatment protection: the purpose is full aftertreatment device protection
Cold start: high level of fluidity at low temperature
Fuel economy: the purpose is good fuel economy and low exhaust emissions

SPECIFICATIONS

FORD	WSS-M2C954-A1

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Kinematic viscosity at 40°C	ASTM D445	mm²/s	43
Kinematic viscosity at 100°C	ASTM D445	mm²/s	8.5
Viscosity index	ASTM D2270		179
Pour point	ASTM D6892	°C	-36
Sulfated Ash	ASTM D874	Mass %	0.78
Flashpoint PMCC	ASTM D93	°C	202
Density at 15°C	ASTM D4052	g/ml	0.841

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV