DRIVEN BY POSSIBILITY™



UREA HOSE

HOSE INNOVATION LEADS THE WAY

As the pace of automotive change continues to accelerate, Gates works with the world's major automotive manufacturers to develop more efficient engine systems to decrease fuel consumption and reduce emissions.

Our reputation as a reliable brand with an established OE pedigree means we can design replacement parts that match the OE specifications you want to fit. Made from proven OE quality materials and fitted with the OE equivalent connectors, they are engineered with quality for a wide range of applications increasingly in demand.

Gates uses innovative materials and designs to keep your engines running at a temperature that's safe, effective, and efficient. By sourcing durable materials, we ensure your electric coolant valves operate at the highest levels possible.

For reliability with OE quality, choose Gates.

FEATURES + BENEFITS

- Complementary product groups for fuel transfer and emission control systems
- Transfer of urea solutions such as **AdBlue®*** used in exhaust treatment of diesel engines equipped with **selective catalytic reduction (SCR) technology**
- Most demanded diameters with optimum lengths for European Market
- Designed with **high-quality materials** for long service life
- Temperature resistance is **-40°C to +125°C**
- The components are a **Zinc-free peroxide-cured EPDM tube**, synthetic fiber reinforcement, and EPDM cover

*AdBlue is a registered trademark of VDA Verband der Automobilindustrie e.V.

ASK YOUR SALES REPRESENTATIVE FOR MORE INFORMATION

GATES TECHZONE | **GATES NaviGates** | **GATES LINKEDIN**

LIVE WEBINARS

SUBSCRIBE BY CLICKING OR SCANNING HERE AND GET YOUR TEAM READY TO LEARN

APPLICATION

					WORK PRESSURE MAX.			BURST MIN			VACUUM MIN		BEND RAD	WEIGHT
ARTICLE NR	PN	ID (mm)	OD (mm)	L (m)	MPa	BAR	PSI	MPa	BAR	PSI	kPa	BAR	MM	KG/M
DEF500-64X15	4217-00007	6.4	12.7	15	3.45	34.5	500	13.79	137.9	2000	95	0.95	76	0.15
DEF350-95X15	4217-10302	9.5	16.8	15	2.41	24.1	350	6.86	68.6	1000	95	0.95	76	0.42
DEF350-127X15	4217-00303	13	23.9	15	2.41	24.1	350	6.86	68.6	1000	95	0.95	76	0.42
DEF350-191X10	4217-00310	19.1	28.5	10	2.41	24.1	350	6.86	68.6	1000	51	0.51	102	0.48
DEF350-254X10	4217-00311	25.4	34.5	10	2.41	24.1	350	6.86	68.6	1000	34	0.34	152	0.61

©2024 Gates

GATES.COM
E2/70666