

WOLF ANH CA GREASE EP 2 GREEN

25/09/2026
9284

This lithium-free multipurpose grease is an anhydrous calcium (ANH Ca) thickened lubricating grease based on a mineral oil and polymer.

The grease contains antioxidants, corrosion inhibitors and EP/AW additives.

APPLICATIONS

The ANH Ca thickener, together with the special base oil blend, makes the product suitable for the lubrication of medium loaded bearings and in wet and corrosive environments.

The lubricating grease has excellent adhesion and water resistance.

FEATURES

Corrosion protection: very good corrosion protection

Multi-applicability: wide range of applications

Water resistance: high resistance against water washout

SPECIFICATIONS

DIN	51502	ISO	12924
DIN	KP2K-30	ISO	L-XC(F)CIB2

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Texture	Visual		SMOOTH
Colour	VISUAL		GREEN
NLGI Classification	ASTM D217		2
Worked Penetration (60 strokes)	ISO 2137	0.1 mm	265-295
Dropping point	ISO 2176/IP 396	°C	> 140
Four Ball Weld Load	ASTM D2596/ DIN51350:4	N	3200
Base Oil Viscosity at 40 °C	ASTM D7152	cSt	320

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com

