

WOLF RACING OW-40 ESTER

11/08/2023
65513

This full synthetic ester enriched racing lubricant increases engine protection and protects all lubricated parts completely. The powerful formulation covers a large part of the racing car market thanks to its high-end properties. Its great fluidity at low temperatures ensures complete protection of all parts right after starting the engine. It is blue colored.

APPLICATIONS

This lubricant is specifically developed for race engines which operate over a wide range of temperatures and rpm.

FEATURES

Total engine protection: performance in keeping the engine clean.
Driving style: sporty driving.

PERFORMANCE

/ /

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.852
Kinematic viscosity at 100°C	ASTM D445	mm²/s	14.5
Pour point	ASTM D6892	°C	-57
Kinematic viscosity at 40°C	ASTM D445	mm²/s	83.2
Viscosity index	ASTM D2270		182
Colour	VISUAL		DARK BLUE

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com

