

WOLF ESSENTIAL SL/CF 10W40 B4

21/07/2025
75610

This engine oil meets the core requirements of ACEA and API for passenger cars. It offers excellent engine cleanliness and complete protection to all engine components.

APPLICATIONS

Suitable for gasoline and diesel engines with standard aspiration and superchargers. Particularly recommended for direct injection diesel engines, including common rail direct fuel injection systems.

FEATURES

Performance in keeping the engine clean.: Performance in keeping the engine clean.

SPECIFICATIONS

ACEA	A3/B3-16	MB	229.1
ACEA	A3/B4	VW	501 01
API	CF	VW	505 00
API	SL		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.865
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	90.1
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	13.8
Viscosity index	ASTM D2270		155
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	10.1
Pour point	ASTM D6892	°C	-33
Evaporation loss (Noack)	CEC L-040-93(B)	% M/M	10.0

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com

