



#### THE NETHERLANDS



### EEC TYPE-APPROVAL CERTIFICATE

### Communication concerning the:

- type-approval
- extension of type-approval
- refusal of type-approval
- withdrawal of type-approval

of a type of a component (towbar) with regard to Directive (94/20/EEC)

Type-approval number: e4\*94/20\*1090\*01

Reason for extension: Change of vertical load S from 70 to 75 kg

## **SECTION I**

0.1 Make (trade name of manufacturer) : Bosal

0.2. Type and general commercial description(s) : 022541

0.3. Means of identification of type

marked on the component : Approval number

0.3.1. Location of the marking : on type plate

0.5. Name and address of manufacturer : Bosal

postbus 168

4920 AD Made Nederland

0.7. In the case of components and separate technical units, location and method of

affixing of the EEC approval mark : on type plate

0.8. Name(s) and address(es) of assembly plants : See information document

(annex III, item 0.8)



## Type-approval number: e4\*94/20\*1090\*01

## SECTION II

1. Additional information (where applicable)

: see Appendix I

2. Technical service responsible for

carrying out the tests

: RDW

Testbaan|Centrum Talingweg 76 8218 NX Lelystad

3. Date of testreport

: 16-09-1998

4. Number of testreport

: RDW-94/20-0076

5. Remarks (if any)

: see Appendix I

6. Place

: Zoetermeer

7. Date

8.

Signature



- 9. The index to the information package lodged with the competent authority that has granted type-approval, which may be obtained on request, is attached.
  - Application form relating to annex III and annexed drawings
  - Drawings and instructions for attachment
  - Fitting instructions
  - Test report as mentioned in item 4.

## Appendix I

# to EEC type-approval certificate No : e4\*94/20\*1090\*01 concerning the components type-approval of mechanical coupling devices with regard to Directive 94/20/EEC

1.	Additional information		
1.1.	Class of the type of coupling	: A50-X	
1.2.	Categories or types of vehicles for which the device is designed or restricted	: see fitting instructions	
1.3.	Maximum D-value	: 9,60	kN
1.4.	Maximum vertical load S at the coupling point	: <u>75</u>	kg
1.5.	Maximum load U at the fifth wheel coupling point	: <del></del>	ton
1.6.	Maximum V-value	:	kN
1.7.	Instructions for attachment of the coupling type to the vehicle and photographs or drawings of the fitting points at the vehicle given by the manufacturer; additional information if the use of the coupling type is restricted to		

: see fitting instructions

1.8. Information on the fitting of special towing brackets or mounting plates

special types of vehicles

: see fitting instructions .

5. Remarks

: The installation of the coupling device to the vehicle must be checked according to requirements of Annex VII, see Annex I, par.5.10.

