WOLF OFFICIALTECH
10W30 MS EXTRA

06/10/2026
15755

This heavy-duty diesel engine oil is a semi-synthetic lubricant offering exceptional wear resistance. It is capable of maintaining its original composition thanks to its outstanding oxidation resistance, shear resistance and aeration control, giving it an increased drain interval compared to previous formulations.

APPLICATIONS

Both modern and older engines benefit from the backward compatible heavy-duty diesel engine oil for most OEMs, making it a perfect match for a wide range of engine types. It is capable of offering optimal protection to a range of Caterpillar, Mack, Renault, Volvo and other market-leading engines with or without after-treatment system, turbocharger or supercharger. It is compatible with emission control technology EURO IV, V and VI for trucks; as well as stage IIIB, IV and Tier 4i, 4f for heavy-duty off-road.

FEATURES

Engine cleanliness: consistent vehicle uptime
Wear protection: high level of protection against wear
Oxidative stability: great oil performance

SPECIFICATIONS

ACEA	E11	DEUTZ	DQC-III-10 LA
ACEA	E7	DEUTZ	DQC-III-18 LA
ACEA	E9-16	DTFR	15C100
API	CI-4	DTFR	15E100
API	CI-4 Plus	FORD	WSS-M2C171-F1
API	CJ-4	JD	JDQ-78X
API	CK-4	MACK	approval EO-S 4.5
API	SN	MACK	EO-M PLUS
CHINESE STANDARD	D1	MACK	EO-N
JASO	DH-1	MACK	EO-N Premium Plus
JASO	DH-2	MACK	EO-O Premium Plus
ALLISON	C4	MAN	M3575
CATERPILLAR	ECF-1a	MAN	M3775
CATERPILLAR	ECF-2	MTU	Oil Category 2.1
CATERPILLAR	ECF-3	RENAULT	approval RLD-3
CATERPILLAR	TO-2	RENAULT	RGD
CUMMINS	CES 20076	RENAULT	RLD
CUMMINS	CES 20077	RENAULT	RLD-2
CUMMINS	CES 20078	RENAULT	RLD-4
CUMMINS	CES 20081	RENAULT	RXD
CUMMINS	CES 20086	VOLVO	approval VDS-4.5
CUMMINS	CES 20100	VOLVO	VDS-3
DAF	PSQL 2.1 E	VOLVO	VDS-4
DETROIT DIESEL	DFS 93K215		
DETROIT DIESEL	DFS 93K218		
DETROIT DIESEL	DFS 93K222		

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.8583
Kinematic viscosity at 40°C	ASTM D445	mm^2/s	70.90
Kinematic viscosity at 100°C	ASTM D445	mm^2/s	11.45
Viscosity index	ASTM D2270		155
B.N. (HCLO4 method)	ASTM D2896	mg KOH/g	9.8
Pour point	ASTM D6892	°C	-36
Sulfated Ash	ASTM D874	Mass %	1.0
Flash Point COC	ASTM D92	°C	232

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com