# WOLF OFFICIALTECH
# 5W-30 C2/C3 EXTRA

14/07/2026
65666

This API SQ synthetic based engine oil is based on carefully selected very high quality base oils, formulated using the latest technology for catalyst compatible engine oils. Its special formulation combines fuel economy with an extended service life. The reduced ash formulation protects particulate filters and exhaust after-treatment devices.

## APPLICATIONS

This dexos™ 2 is required for all new GM/Opel/Vauxhall/Chevrolet diesel and gasoline models. GM/Opel has advised that the dexos™ 2 specification is backward compatible to older GM/Opel specifications (GM-LL-A-025 and GM-B-LL-025). The majority of GM/Opel/Vauxhall/Chevrolet diesel and gasoline vehicles can use dexos™ 2 lubricants.
Broad application field with both ACEA C3 (German OEM's) / C2 (PSA) and also covering API SQ.

## FEATURES

Aftertreatment protection: full aftertreatment device protection.
Fuel economy: lower fuel consumption and CO2 emissions.
Total engine protection: outstanding engine cleanliness and durability.

## SPECIFICATIONS

| | | | |
|---|---|---|---|
| ACEA | C2 | PSA | B71 2290-2014 |
| ACEA | C3 | RENAULT | RN 0700 |
| API | SN | RENAULT | RN 0710 |
| API | SN Plus | RENAULT | RN17 Level |
| API | SP | VW | 502 00 < 2017 |
| API | SQ | VW | 505 00 |
| BMW | approval LONGLIFE-04 | VW | 505 01 |
| CHRYSLER | MS 11106 | | |
| FIAT | 9.55535-S1 | | |
| FIAT | 9.55535-S3 | | |
| FORD | WSS-M2C917-A | | |
| GM | dexos™1 Gen 2 | | |
| GM | dexos™1 Gen 3 | | |
| GM | dexos™2 | | |
| HYUNDAI | SFU | | |
| IVECO | 18-1811 Classe SC1 | | |
| KIA | SFU | | |
| MB | 226.52 | | |
| MB | 229.31 | | |
| MB | 229.51 | | |
| MB | 229.52 | | |
| OPEL | GM-LL-A-025 | | |
| OPEL | GM-LL-B-025 | | |
| OPEL | OV 040 1547 - D30 | | |
| OPEL | OV 040 1547 - G30 | | |

**WOLF OIL CORPORATION NV**
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com



The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

## TYPICAL CHARACTERISTICS

| Test | Method | Unit | Average results |
|---|---|---|---|
| Density at 15°C | ASTM D4052 | g/ml | 0.852 |
| Kinematic viscosity at 40°C | ASTM D445 | $mm^2/s$ | 71.5 |
| Kinematic viscosity at 100°C | ASTM D445 | $mm^2/s$ | 12.2 |
| Viscosity index | ASTM D2270 | | 169 |
| B.N. (HCLO4 method) | ASTM D2896 | mg KOH/g | 7.6 |
| Pour point | ASTM D6892 | °C | -39 |
| Flash Point COC | ASTM D92 | °C | 220 |

**We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.**

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

**WOLF OIL CORPORATION NV**
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com