WOLF OE LEVELTECH 0W-20 IL D1

25/09/2026
75649

Thanks to its low viscosity and outstanding fluidity this oil significantly reduces wear and ensures fuel savings and lower CO2 emissions. Optimized additive package reduces soot and deposits and keeps the engine clean. It is suitable for hybrid cars when the OEM specifications are met.

APPLICATIONS

This engine oil has been specifically developed to meet the challenging requirements of the latest GM Dexos1 Gen 3 specification and ILSAC GF-7 A standard where fuel economy and CO2 reduction are important. It provides the performance needed for the most recent requirements for gasoline-fueled US and Asian passenger cars.

FEATURES

Cold start: high level of fluidity at low temperature
Fuel economy: the purpose is an efficient fuel economy and very low exhaust emissions
Engine protection: ensures high level of the engine cleanliness

SPECIFICATIONS

API	SN	GM	4718M
API	SN Plus	GM	6094M
API	SN/RC	GM	dexos™1 Gen 3
API	SP	GMC	SFU
API	SP/RC	HONDA	SFU
API	SQ	HYUNDAI	SFU
API	SQ/RC	INFINITI	SFU
ILSAC	GF-4	JAECO	SFU
ILSAC	GF-5	KIA	SFU
ILSAC	GF-6 A	LEXUS	SFU
ILSAC	GF-7 A	LINCOLN	SFU
ACURA	SFU	LOTUS	SFU
ASTON MARTIN	SFU	MAZDA	SFU
BUICK	SFU	MG	SFU
BYD	SFU	MITSUBISHI	SFU
CADILLAC	SFU	OMODA	SFU
CHEVROLET	SFU	PERODUA	SFU
CHRYSLER	MS 6395	ROEWE	SFU
DODGE	SFU	SCION	SFU
EBRO	SFU	SUZUKI	SFU
FIAT	9.55535-CR1	TATA	SFU
FIAT	9.55535-GSX	TIANJIN	SFU
FORD	WSS-M2C930-A	TOYOTA	SFU
FORD	WSS-M2C945-A		
FORD	WSS-M2C946-A		
FORD	WSS-M2C947-A		
FORD	WSS-M2C962-A1		

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.847
Kinematic viscosity at 40°C	ASTM D445	mm^2/s	45.6
Kinematic viscosity at 100°C	ASTM D445	mm^2/s	8.5
Viscosity index	ASTM D2270		166
B.N. (HCLO4 method)	ASTM D2896	mg KOH/g	7.2
Pour point	ASTM D6892	°C	-39
Flash Point COC	ASTM D92	°C	215

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV