WOLF OFFICIALTECH
10W40 S3

25/09/2026
1727

This is a semi synthetic lubricant based on carefully selected very high quality base oils. This "long-drain" oil is engineered to provide outstanding lubrication to modern, high performance diesel engines.

APPLICATIONS

This oil is suitable for Euro IV and Euro V engines. Due to the high ash content, this oil is not suitable for most engines and vehicles equipped with a particulate filter.

FEATURES

Emission: the purpose is to minimise exhaust emission
Engine protection: high level of engine cleanliness and durability
Cold start: very good fluidity at low temperature

SPECIFICATIONS

ACEA	E4
ACEA	E7
API	CF-4
API	CG-4
API	CH-4
API	CI-4/SL
JASO	DH-1
ALLISON	C4
CATERPILLAR	ECF-1a
CATERPILLAR	ECF-2
CATERPILLAR	TO-2
CUMMINS	CES 20072
CUMMINS	CES 20076
CUMMINS	CES 20077
CUMMINS	CES 20078
DAF	EXTENDED DRAIN
DETROIT DIESEL	DFS 93K215
DEUTZ	DQC-III-10
DEUTZ	DQC-III-18
DEUTZ	DQC-IV-18
DTFR	13D100
DTFR	13D110
DTFR	15B110
DTFR	15B120
GLOBAL	DHD-1
IVECO	18-1804 Classe T2 E7
IVECO	18-1804 Classe T3 E4
MACK	approval EO-N
MACK	EO-M PLUS
MACK	EO-N Premium Plus
MAN	M3275-1
MAN	M3277
MAN	M3377
MB	229.1
MB	235.28
MTU	Oil Category 1
MTU	Oil Category 2
MTU	Oil Category 3
RENAULT	approval RLD-2
RENAULT	RLD
RENAULT	RXD
SCANIA	approval LDF-3
SCANIA	LDF-2
VOITH	Retarder Oil Class A
VOITH	Retarder Oil Class B
VOLVO	approval VDS-3

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.870
Kinematic viscosity at 40°C	ASTM D445	mm^2/s	86.3
Kinematic viscosity at 100°C	ASTM D445	mm^2/s	13.3
Viscosity index	ASTM D2270		155
B.N. (HCLO4 method)	ASTM D2896	mg KOH/g	16.1
Pour point	ASTM D6892	°C	-39
CCS viscosity at -25°C	ASTM D5293	mPa.s	6700
Sulfated Ash	ASTM D874	Mass %	1.9
Flash Point COC	ASTM D92	°C	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com