



1. IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Trade Name:

VAICO VA-DOT 4 LV

VAICO No.:

V60-0317, V60-0318, V60-0319, V60-0320

1.2. Informing department

VIEROL AG | Karlstraße 19 | 26123 Oldenburg | Germany

Telefon +49 441 - 210 20-0 | Telefax +49 441 - 210 20-111

2. PROPERTIES

Suitable for brake and clutch systems where the DOT4 Class 6 is required. Because of its low viscosity, it is recommended for brake systems with ABS, ESP/DSC and TCS. Can be mixed with all synthetic brake fluids of the same grade. Guarantees perfect operating of the braking system even at low temperatures. Based on polyglycol ether

2.1. Special instructions:

- 2.1.1. Store brake fluid only in sealed original container.
- 2.1.2. Brake fluid can cause damage to vehicle paintwork.
- 2.1.3. Observe manufacturer instructions!

3. PERFORMANCE DATA

Specifications:

FMVSS 116 DOT 3 / DOT 4

SAE J 1703 / J 1704

ISO 4925 Class 6

Suitable for:*

AUDI-VW B 000 750, VW 501 14, VW TL 766-Z | **BMW** QV 34 001 | **FORD** WSS-M6C65-A2

GM Europe GMW 3356 | **PSA** STL S71 2114

TYPICAL VALUES	METHOD	UNIT	VAICO VA-DOT 4 LV
Density at 20°C	DIN 51 757	g/cm ³	1.60
Viscosity at -40°C	DIN ISO 3104	mm ² /s	Max. 700
Dry boiling point (min.)	DIN ISO 4925	°C	265
Wet boiling point (min.)	DIN ISO 4925	°C	170

* conforms to OEM specifications – The above values may vary within commercially accepted tolerances.