WOLF OFFICIALTECH
DCT FLUID

25/09/2026
5099

This is a lubricant based on carefully selected very high quality base oils, specifically developed for the dual clutch transmissions (DCT) of modern passenger cars. It ensures trouble-free operation of these gearboxes.

APPLICATIONS

Mainly intended for the DCT of VAG, this fluid can also be used for other 6-speed DCT transmissions, such as Chrysler Powershift, Ford Powershift, Mitsubishi TC-SST, Volvo Powershift,BMW Drivelogic 7-speed, etc.

FEATURES

Anti-wear protection: long transmission life
Oil life durability: high level of thermal and oxidation stability
Frictional properties: very smooth gear shifting, no vibration

SPECIFICATIONS

API	GL-4	CHRYSLER	68044345EA
BORGWARNER	WET DCT	CHRYSLER	68044345GA
BENTLEY	G 052 524-B2	CHRYSLER	Powershift 6 speed
BMW	6 speed DCT	DTFR	13C130
BMW	83 22 2 446 673	FERRARI	7 Speed (Getrag)
BMW	83 22 5 A53 CB2	FERRARI	TF DCT-F3
BMW	83220306816	FIAT	9.55550-DA11
BMW	83220397244	FIAT	9.55550-HE2
BMW	83220440214	FIAT	9.55550-MZ2
BMW	83222147477	FIAT	9.55550-MZ6
BMW	83222148578	FORD	1 490 761
BMW	83222148579	FORD	1 490 763
BMW	83222167666	FORD	F-DC
BMW	83222409710	FORD	MU7J 19A509 AA
BMW	83222433157	FORD	WSS-M2C200-D2
BMW	83225B3AC81	FORD	WSS-M2C200-D3
BMW	DCTF-1	FORD	WSS-M2C200-E1
BMW	DCTF-1+	FORD	WSS-M2C218-A1
BMW	DCTF-2	FORD	WSS-M2C936-A
BMW	Drivelogic 7 speed	GM	DEXRON DCT
BMW	DTF 1	GM	FFL-4
BMW	FFL-4	GREAT WALL	GW7DCT1
BMW	MTF LT-3	GREAT WALL	GWM 7DCT450
BMW	MTF LT-5	HONDA	MTF III
BUGATTI	VEYRON (wet DCT)	HONDA	TYPE 2
BYD	6DT35	HYUNDAI	04300-2N100
BYD	QVBYD-A1909.0058.2013	HYUNDAI	04300-2N110 WDHO-1
CHANGAN	DCTF	KIA	04300-2N100
CHERY	730DHB/DHC 7DCT300	KIA	04300-2N110 WDHO-1
CHERY	738DHA 7DCT380	KUNLUN	DCTF-7S
CHERY	9009011085	MB	000 989 20 02

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV

MB	000 989 61 04
MB	001 989 85 03
MB	001 989 86 03
MB	002 989 04 03
MB	236.21
MB	236.22
MB	236.24
MB	236.25
MB	239.21
MB	239.22
MB	SLS A0019898603
MCLAREN	FFL-4
MITSUBISHI	DIAMOND QUEEN SSTF-1
MITSUBISHI	MZ320065
NISSAN	999MP-6TRT00P
NISSAN	DCT FLUID
NISSAN	GR6
NISSAN	GT-R R35
NISSAN	LV MT-1
NISSAN	R35 SPECIAL
PKD	DCT Transmission Oil for ZF
PORSCHE	000.043.20
PORSCHE	000.043.207.29
PORSCHE	000.043.207.30
PORSCHE	000.043.210.44
PORSCHE	000.043.305.63
PORSCHE	971.094.307.02A
PORSCHE	999.917.080.00
PORSCHE	999.917.080.01
PORSCHE	999.917.546.00
PORSCHE	TF 0870
PSA	1618078480
PSA	9730 A8
PSA	9734 S2
PSA	JWS 2271
PUNCH	DT2
RENAULT	7711579456
RENAULT	7711785243
RENAULT	BOT450 EDC 6-Speed
RENAULT	DC4
RENAULT	DW5
RENAULT	DW6
RENAULT	EDC
SINOPEC	DCTF-GS
STELLANTIS	16 934 837 80
SUZUKI	99000-22B27-036
TOYOTA	0888581001
TOYOTA	JWS 2271
TOYOTA	LF
TOYOTA	LV 75W MT
VOLVO	1161520-7
VOLVO	1161838
VOLVO	1161839
VOLVO	32240415
VOLVO	32240419
VOLVO	BOT341 #1161838
VOLVO	D1
VOLVO	D2
VW	G 052 171
VW	G 052 178
VW	G 052 182
VW	G 052 512
VW	G 052 513
VW	G 052 524
VW	G 052 527
VW	G 052 529
VW	G 052 536
VW	G 052 726
VW	G 052 798
VW	G 055 512
VW	G 055 524
VW	G 055 529
VW	G 055 536
VW	G 055 549
VW	G 060 726
VW	G 070 726
VW	G009317
VW	TL 521 82
ZF	0671090545
ZF	TE-ML 11

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.853
Kinematic viscosity at 40°C	ASTM D445	mm²/s	35.7
Kinematic viscosity at 100°C	ASTM D445	mm²/s	7.26
Viscosity index	ASTM D2270		173
Pour point	ASTM D6892	°C	-39
Flash Point COC	ASTM D92	°C	202

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV