WOLF OFFICIALTECH
MULTI ATF HD-AL

25/09/2026
3030

This full synthetic automatic transmission fluid is designed to deliver durable extended drain performance in Allison on-highway and hybrid automatic transmissions.

APPLICATIONS

This is a robust Allison TES 668 and TES 295 fluid for severe service. Also in line with the corresponding Daimler Trucks Fluid Release (DTFR) specifications.

FEATURES

Anti-wear protection: long transmission life
Oil life durability: high level of thermal and oxidation stability
Frictional properties: smooth shift performance

SPECIFICATIONS

ALLISON	TES 295	MB	236.91
ALLISON	TES 468	MB	236.92
ALLISON	TES 668	VOITH	H55.6336xx
DTFR	13C180	ZF	TE-ML 14C
DTFR	13C190		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.857
Kinematic viscosity at 40°C	ASTM D445	mm^2/s	33.3
Kinematic viscosity at 100°C	ASTM D445	mm^2/s	7.14
Viscosity index	ASTM D2270		186
B.N. (HCLO4 method)	ASTM D2896	mg KOH/g	4.0
Pour point	ASTM D6892	°C	-45
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV